UltraCare Sealer for Glass Tiles & Shower Doors





DESCRIPTION

UltraCare[®] Sealer for Glass Tiles & Shower Doors is specifically designed to keep glass tiles and shower doors cleaner for longer. This easy-to-use formula uses advanced chemical technology that becomes part of the surface, creating a barrier that causes water to bead and slide off glass surfaces. Continued use of this product helps to repel the buildup of soap scum, calcium, hard water deposits and grime onto glass surfaces, significantly reducing cleaning time and effort.

FEATURES AND BENEFITS

- Transparent hydrophobic barrier technology helps to reduce soap scum, calcium, hard water deposits and grime from building up on and sticking to glass surfaces
- Makes cleaning of hard water and other contaminants quicker and easier
- Keeps glass cleaner, eliminating the need for harsh cleaners that may damage glass surfaces over time
- Does not streak or smear
- UV-stable

WHERE TO USE

- Tubs and shower doors in bathrooms
- Glass tiles and glass surfaces in kitchens and bathrooms
- Interior and exterior glass surfaces

LIMITATIONS

- Do not thin or dilute the product.
- Use in a well-ventilated area.
- Do not use on non-recommended surfaces.

PRODUCT APPLICATION

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details. Read all installation instructions thoroughly before installation.

Due to variations between surfaces, sample testing is recommended to maximize performance and suitability for intended use.

- 1. Ensure that the surface is clean, dry and prepared for product application.
- 2. Spray the product onto the glass surface or onto a new microfiber towel. Wipe the glass using a firm, circular and overlapping motion.
- 3. Allow the surface to dry until a slight haze appears.
- 4. Repeat Step 2 to ensure complete and uniform coverage.
- 5. Remove the final haze with a dry microfiber towel or dry cloth until glass is crystal clear.
- 6. If streaking or hazing is still noticeable, rebuff with a wet microfiber towel or damp cloth.
- 7. Reapply the product as often as needed to help keep glass clean typically once every 2 to 4 weeks.

PROTECTION

- Protect such non-glass exposed surfaces as wood, carpet and landscaping before product use.
- Keep the container closed tightly when the product is not in use.
- Keep out of reach of children and pets.
- Do not get in the eyes. If this product gets in the eyes, rinse with running water for several minutes. If irritation persists, seek medical attention.
- Store at room temperature in the original container. Do not freeze. Keep away from heat, sparks and open flames.

Shelf Life and Product Characteristics

Shelf life	5 years when stored in original, unopened packaging at 73°F (23°C)
Physical state	Liquid
Color	Clear
VOCs	< 0.75 g per L

Packaging

Size

Spray bottle: 12 U.S. oz. (355 mL)

Approximate Coverage*

per 12 U.S. oz. (355 mL)

Coverage

Up to $135 \text{ sq. ft.} (12.5 \text{ m}^2)$

* Coverage varies depending on surface finish and texture.

ADDITIONAL INFORMATION

Refer to the SDS for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. <u>ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.</u>

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive Deerfield Beach, Florida 33442 1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

<u>U.S. and Puerto Rico:</u>
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:

1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: May 10, 2023 MK 11021 (23-1704)

For the most current product data and BEST-BACKEDSM warranty information, visit www.mapei.com.

All Rights Reserved. © 2023 MAPEI Corporation.

