



## Material Safety Data Sheet

### 1 - Chemical Product and Company Identification

<b>Manufacturer:</b> WD-40 Company <b>Address:</b> 1061 Cudahy Place (92110) P.O. Box 80607 San Diego, California, USA 92138 -0607 <b>Telephone:</b> <b>Emergency only:</b> 1-888-324-7596 (PROSAR) <b>Information:</b> 1-888-324-7596 <b>Chemical Spills:</b> 1-800-424-9300 (Chemtrec) 1-703-527-3887 (International Calls)	<b>Trade Name:</b> WD-40 Specialist Protective White Lithium Grease (Low VOC)  <b>Chemical Name:</b> Organic Mixture  <b>Product Use:</b> Cleaner, Lubricant  <b>MSDS Date Of Preparation:</b> 01/23/14
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### 2 – Hazards Identification

#### Emergency Overview:

**DANGER!** Extremely flammable aerosol. Contents under pressure. Combustible Liquid and Vapor. Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. May cause eye, skin and respiratory tract irritation. Use only with adequate ventilation. Keep away from heat, sparks, flames and all other sources of ignition.

#### Symptoms of Overexposure:

**Inhalation:** Mist or vapor can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

**Skin Contact:** May cause skin irritation with short-term exposure with redness, itching and burning of the skin. Prolonged and/or repeated contact may produce defatting and dermatitis.

**Eye Contact:** Contact may be irritating to eyes. May cause redness, stinging, swelling and tearing.

**Ingestion:** This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

**Chronic Effects:** Prolonged or repeated skin contact may defat the skin resulting in irritation and dermatitis.

**Medical Conditions Aggravated by Exposure:** Preexisting eye, skin and respiratory conditions may be aggravated by exposure.

#### Suspected Cancer Agent:

Yes X No This product contains small amount of titanium dioxide, which is listed by IARC as a suspected carcinogen (Group 2B). Titanium dioxide only presents a risk of cancer by inhalation of very fine dust. In this product, the titanium dioxide is incorporated into the grease and is not present as a respirable dust. There is no exposure to respirable titanium dioxide dust in the normal use of this product.

### 3 - Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent
Petroleum Solvents (LVP)	64742-47-8 64742-88-7	55-65%
Propellant (Propane)	74-98-6	<25%
Hydrotreated Heavy Naphthenic Distillate	64742-52-5	<6%
Solvent-refined Heavy Paraffinic Petroleum Distillates	64741-88-4	<6%
Calcium Sulfonate	Proprietary	1-5%
Titanium Dioxide	13463-67-7	<3%

See Section 8 for Exposure Limits

#### 4 – First Aid Measures

**Ingestion (Swallowed):** Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

**Eye Contact:** Flush thoroughly with water for 15 minutes. Remove contact lenses if present after the first 5 minutes and continue flushing. Get medical attention if irritation persists.

**Skin Contact:** Wash with soap and water. If irritation develops and persists, get medical attention.

**Inhalation (Breathing):** If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

#### 5 – Fire Fighting Measures

**Extinguishing Media:** Use water fog, dry chemical, carbon dioxide or foam. Cool fire exposed containers with water.

**Special Fire Fighting Procedures:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

**Unusual Fire and Explosion Hazards:** Contents under pressure. Keep away from ignition source and open fire. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Flammable liquid and vapor. This material can release flammable vapors when heated above ambient temperatures. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces.

#### 6 – Accidental Release Measures

Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area. Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

#### 7 – Handling and Storage

**Handling:** Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.

**Storage:** Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol.

#### 8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure Limits
Petroleum Solvents	1200 mg/m <sup>3</sup> TWA Supplier Recommended (total hydrocarbon)
Propane	1000 ppm TWA OSHA PEL
Hydrotreated Heavy Naphthenic Distillate	5 mg/m <sup>3</sup> TWA (inhalable) ACGIH TLV (as Mineral oil) 5 mg/m <sup>3</sup> TWA OSHA PEL (as Oil mist)
Solvent-refined Heavy Paraffinic Petroleum Distillates	5 mg/m <sup>3</sup> TWA (inhalable) ACGIH TLV (as Mineral oil) 5 mg/m <sup>3</sup> TWA OSHA PEL (as Oil mist)
Calcium Sulfonate	None Established
Titanium Dioxide	10 mg/m <sup>3</sup> TWA ACGIH TLV 15 mg/m <sup>3</sup> (total dust) TWA OSHA PEL

**The Following Controls are Recommended for Normal Consumer Use of this Product**

**Engineering Controls:** Use in a well-ventilated area.

**Personal Protection:**

**Eye Protection:** Avoid eye contact. Always spray away from face.

**Skin Protection:** Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where prolonged skin contact is likely.

**Respiratory Protection:** None needed for normal use with adequate ventilation.

**For Bulk Processing or Workplace Use the Following Controls are Recommended**

**Engineering Controls:** Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

**Personal Protection:**

**Eye Protection:** Safety goggles recommended where eye contact is possible.

**Skin Protection:** Wear chemical resistant gloves.

**Respiratory Protection:** None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

**Work/Hygiene Practices:** Wash with soap and water after handling.

**9 – Physical and Chemical Properties**

Boiling Point:	221-271°C (430-520°F) (Petroleum Solvent)	Specific Gravity:	0.87
Solubility in Water:	Insoluble	pH:	Not Applicable
Vapor Pressure:	0.009 kPa (0.07 mm Hg) at 20 C	Vapor Density:	5.3 (Petroleum Solvent)
Percent Volatile:	<25%	VOC:	24.72%
Coefficient of Water/Oil Distribution:	Not Determined	Appearance/Odor	Colorless liquid with a petroleum odor.
Flash Point:	<-30°C (-22°F) (CC ASTM D3828)	Flammable Limits:	LEL: 0.6% UEL: 5% (Petroleum Solvent)

**10 – Stability and Reactivity**

**Stability:** Stable

**Hazardous Polymerization:** Will not occur.

**Conditions to Avoid:** Avoid heat, sparks, flames and other sources of ignition.

**Incompatibilities:** Strong acids, alkalis, and oxidizers.

**Hazardous Decomposition Products:** Carbon monoxide and carbon dioxide, oxides of nitrogen and sulfur, smoke, fumes, and/or unburned hydrocarbons.

**11 – Toxicological Information**

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

This product contains small amount of titanium dioxide, which is listed by IARC as a suspected carcinogen (Group 2B). Titanium dioxide only presents a risk of cancer by inhalation of very fine dust. In this product, the titanium dioxide is incorporated into the grease and is not present as a respirable dust. There is no exposure to respirable titanium dioxide dust in the normal use of this product.

None of the components of this product is considered a reproductive hazard.

**12 – Ecological Information**

No data is currently available.

### 13 - Disposal Considerations

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate containers.

### 14 – Transportation Information

DOT Surface Shipping Description: Consumer Commodity, ORM-D  
After 1/1/2014 UN1950, Aerosols, 2.1 Ltd. Qty (Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)  
IMDG Shipping Description: UN1950, Aerosols, 2.1, LTD QTY  
ICAO Shipping Description: UN1950, Aerosols, flammable, 2.1 NOTE: WD-40 does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

### 15 – Regulatory Information

#### U.S. Federal Regulations:

**CERCLA 103 Reportable Quantity:** This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

#### SARA TITLE III:

**Hazard Category For Section 311/312:** Acute Health, Fire Hazard, Sudden Release of Pressure

**Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III

Section 313 Reporting requirements: None

**Section 302 Extremely Hazardous Substances (TPQ):** None

**EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory

**VOC Regulations:** This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):** This product does not contain chemicals regulated under California Proposition 65. While this product contains titanium dioxide, it is not in a respirable form and is bound in the grease so no exposure occurs under normal conditions of use.

**Canadian Environmental Protection Act:** All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification

**Canadian WHMIS Classification:** Class B-5 (Flammable Aerosol), Class D-2-A (Very toxic material causing other chronic effects)

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

### 16 – Other Information:

#### HMIS Hazard Rating:

**Health – 1\* (slight hazard), Fire Hazard – 4 (severe hazard), Physical Hazard – 0 (minimal hazard)**

Prepared by: Industrial Health and Safety Consultants, Inc., Shelton, CT.

SIGNATURE: IJK

TITLE: Regulatory Affairs Manager

REVISION DATE: January 2014

SUPERSEDES: November 2013

2025200 / No. 0089202