



52141-1/2




52151-1/2




52151-3/4




52151-1/2 &amp; 3/4




52151-1/2 &amp; 3/4




52151-3/4-W










52151-1/2 &amp; 3/4-EW



52151-1/2 &amp; 3/4-EWGB



52151-1/2 &amp; 3/4-EWP

52151-B-1/2 & 3/4  
"B" Bracket mounted flush52151-MS-1/2 & 3/4  
For use on 1 1/2", 2 1/2",  
3 3/4", 4", 6" metal studs52151-V-1/2 & 3/4  
"SV" Bracket  
mounted flush52151-CV-3/4  
"CV" Bracket  
mounted flush52151-CV-1/2 & 3/4  
"CV" Bracket  
mounted flush52151-DV-1/2  
"DV" Bracket  
provides offset

52151-EF-SSX

## 4" Square Boxes

Cat. No.	Brkts.	Knockouts			Std. Ctn.
		Ea. Side Conduit	Ea. End Conduit	Bottom Cable	
<b>1 1/4" deep—with conduit KOs—18.0 cubic inch capacity</b>					
52141-1/2	—	2-1/2"	3-1/2"	5-1/2"	50
<b>1 1/2" deep—with conduit KOs—21.0 cubic inch capacity drawn</b>					
52151-1/2	—	3-1/2"	3-1/2"	5-1/2"	50
52151-3/4	—	2-3/4"	2-3/4"	3-1/2" 2-3/4"	50
52151-1/2 & 3/4	—	2-1/2" 1-3/4"	2-1/2" 1-3/4"	3-1/2" 2-3/4"	50
52151-1/2 & 3/4P	—	2-1/2" 1-3/4"	2-1/2" 1-3/4"	3-1/2" 2-3/4"	50
52151-3/4-W	—	2-3/4"	2-3/4"	3-1/2" 2-3/4"	50
52151-B-1/2 & 3/4*	B	2-1/2" 1-1/2" & 3/4E	2-1/2" 1-3/4" & 3/4E	3-1/2" 2-1/2" & 3/4E	25
52151-1/2 & 3/4-EW*	H	2-1/2" 1-1/2" & 3/4E	2-1/2" 1-1/2" & 3/4E	3-1/2" 2-1/2" & 3/4E	50
52151-1/2 & 3/4-EWGB (Ground Bump)	H	2-1/2" 1-1/2" & 3/4E	2-1/2" 1-1/2" & 3/4E	2-1/2" 2-1/2" & 3/4E	50
52151-1/2 & 3/4-EWGBP (Ground Bump with 10 1/2" Ground Wire)	H	2-1/2" 1-1/2" & 3/4E	2-1/2" 1-1/2" & 3/4E	2-1/2" 2-1/2" & 3/4E	50
52151-1/2 & 3/4-EWP*	H	2-1/2" 1-1/2" & 3/4E	2-1/2" 1-1/2" & 3/4E	3-1/2" 2-1/2" & 3/4E	50
52151-MS-1/2 & 3/4*	MS	2-1/2" 1-1/2" & 3/4E	2-1/2" 1-3/4" & 3/4E	3-1/2" 2-1/2" & 3/4E	25
52151-V-1/2 & 3/4*	SV	2-1/2" 1-1/2" & 3/4E	2-1/2" 1-3/4" & 3/4E	3-1/2" 2-1/2" & 3/4E	25
52151-CV-3/4	CV	2-3/4"	2-3/4"	3-1/2"	25
52151-CV-1/2 & 3/4*	CV	2-1/2" 1-1/2" & 3/4E	2-1/2" 1-3/4" & 3/4E	3-1/2" 2-1/2" & 3/4E	25
52151-DV-1/2*	DV	2-1/2" & 3/4E	3-1/2" & 3/4E	3-1/2" & 3/4E	25
52151-EF-SSX	SSX	1-1/2" 1-1/2" & 3/4E	2-1/2" 1-1/2" & 3/4E	2-1/2" 2-1/2" & 3/4E	25

\* Per U.L. 514-A, suitable for use without a bonding jumper in circuits above or below 250 volts.

\* All Bracketed Boxes come complete with eccentric knockouts.

• Pigtail wire is #12 AWG insulated, 10 1/2" long.