

Pasos a Seguir



PASO 1
Para un césped, marcar un círculo de diámetro de 49 pulgadas con pintura de y luego vaya al paso 2. Para un patio, utilice tiza en lugar de pintura y luego vaya al paso 5.



PASO 2
Quite todo el césped, raíces y suciedad a una profundidad de 2 pulgadas dentro del círculo.



PASO 3
Nivelar el suelo y quitar puntos altos de la mejor manera posible. Sugerencia: Utilice un nivel de pequeño para ayudar.



PASO 4
Añada 1 ½ pulgadas de base y use un pisón para anivellar. Humezca con agua para ayudar a la compactación entonces use el pisón nuevamente en el área entera. Añada 5 - 1 pulgada más y use el nivel otra vez.



PASO 5
Coloque el bloque, tocando con firmeza creando un círculo por encima de la base. Asegúrese de que cada piedra este anivellada desde el frente y hacia atrás y de lado a lado e incluso con los bloques adyacentes.



PASO 6
Para la segunda capa de bloques, poner la mitad de cada bloque sobre la articulación entre los dos bloques debajo. Coloque las restas de los bloques firmemente juntos y use el nivel como antes.



PASO 7
Fije las dos capas de bloques juntas usando el pegamento para concreto. Quite un bloke coloque pegamento cerca del centro de cada bloque, y haga presión firmemente. Repita para todas las capas.



PASO 8
Poner la tercera capa del mismo modo que hizo la segunda capa. Las articulaciones de la tercera capa deben alinearse con las articulaciones de la primera capa. Coloque pegamento para concreto como lo hiciste en el paso 7.



PASO 9
Después de terminar la instalación de todos los bloques de su nueva fogata, inserte el anillo de metal. El labio superior de este debe descansar sobre el borde interior de la fogata.



PASO 10
Después de que el pegamento para concreto se seque, vierta la roca de lava en el fondo de su fogata y nivelándolo de lado a lado. La grava debe llegar a la parte inferior del anillo de metal.

How to Guide



STEP 1
For a lawn, mark a 49 inch diameter circle with marking paint then go to step 2. For a patio, use chalk instead of paint then skip to step 5.



STEP 2
Remove all sod, roots and dirt to a depth of 2 inches inside the circle.



STEP 3
Level the soil and remove high spots as best possible. Tip: Use a household level to help.



STEP 4
Add 1 ½ to 2 inches of paver base and level. Moisten with water to aid compaction then use a tamper to pack the entire area firm. Add .5 to 1 inch more of paver base and level again.



STEP 5
Place wall stones on top of paver base, firmly touching each stone creating a circle. Make sure each stone is leveled front to back and side to side and even with adjacent stones.



STEP 6
For the second layer of stone, lay the middle of each stone over the joint made between the sides of the two stones underneath it. Place stones firmly together and level as before.



STEP 7
Attach the two layers of stone together using concrete adhesive. Remove one top stone and lay 2 liberal beads of adhesive near the center of the stone. Place stone back and press down firmly. Repeat for all 2nd layer stones.



STEP 8
Lay the third layer the same way as the second. The third layer joints should line up with the first layer joints. Adhere the stones with concrete adhesive as you did in step 7.



STEP 9
After all stones are set, install the fire pit insert. The insert's top lip should rest on the inside edge of the fire pit stones.




STEP 10
After the adhesive cures, pour lava rock into the bottom of the fire pit, leveling it as you go. The gravel should reach the bottom of the insert ring.




Looking For More Selection?

Visit our customer service desk for a custom assortment of additional products.

¿Buscando Más Selecciones? Visita nuestra área de servicio al cliente para encontrar más variedad de productos personalizados.



See an associate
Consulte a un asociado



View catalog
Consulte el catálogo



Visit Lowes.com
Visite Lowes.com/Español

Project Time:
4 Hours




Difficulty Level
Easy

Available at Lowe's to go.

©2014 Lowe's Companies, Inc. All rights reserved.

Create Your Own
Unique
Firepit.



Wall Block Estimator		Diameter	Accommodates # of People	3 Layers / Capas	4 Layers / Capas	5 Layers / Capas	3 Layers / Capas	4 Layers / Capas	5 Layers / Capas
12-in Flagstone Wall 11-2/8-in x 6-in x 4-in	Style Options  	3.5-ft	3-4	36	48	60	60	72	84
		4-ft	4-5	39	52	65	65	78	91
		6-ft	6-7	51	68	85	85	108	119
		8-ft	8-10	81	108	135	135	162	179
Countryside Wall 8.6-in x 7.5-in x 3.8-in	Style Options  	3.5-ft	3-4	42	56	70	70	84	98
		4-ft	4-5	54	72	90	90	108	126
		6-ft	6-7	66	88	110	110	132	154
		8-ft	8-10	105	140	175	175	210	245
Insignia Wall 12-in x 7-in x 4-in	Style Options  	3.5-ft	3-4	33	44	55	55	66	77
		4-ft	4-5	36	48	60	60	72	84
		6-ft	6-7	57	76	95	95	114	133
		8-ft	8-10	75	100	125	125	150	175
Olde Manor Wall 11.5-in x 7.5-in x 3.5-in	Style Options  	4-ft x 4-ft	3-4	42	56	70	70	84	98
		5-ft x 5-ft	4-5	54	72	90	90	108	126
		4-ft x 6-ft	5-7	54	72	90	90	102	126



Shopping List

Las herramientas que necesitas:

- Wall Block**
Bloques para Pared
- Tamper**
Pizón
- Household Level**
Nivel Pequeño
- 2 Bags of Paver Base**
2 Bolsas de Base para Adoquín
- 2 Tubes of Concrete**
2 Bolsas de Cemento
- Adhesive**
Pega
- Caulk Gun**
Pistola para
- 3 Bags of Lava Rock**
3 Bolsas de Roca de Lava
- Shovel**
Pala
- Optional Marking Paint or Chalk**
Opcional, Pintura o Tiza para Marcar
- Measuring Tape**
Cinta Métrica

Need a
Landscaper?

Visit Porch.com or text
"Landscaper" to 570-225-0005
to find a pro.

Porch