



# SNAPTIGHT

---

## PRODUCTS

★ INSULATED BUILDING PRODUCTS ★

### CARE AND MAINTENANCE GUIDE

All rights reserved.

**WARNING:** Drilling, sawing, sanding or machining SnapTight Products can expose you to particles of dust, a substance known to the State of California to cause cancer. Avoid inhaling the dust particles or use a dust mask or other safeguards for personal protection. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Please review prior to beginning any project.

Always follow manufacturer's installation instructions. Failure to follow manufacturers installation instructions will void manufacturer warranty.

#### **Storage of SnapTight Products Pre-Fabricated Insulated Stucco Building Products as follows:**

##### Prior to Installation:

- Store prefinished products off the ground, under a roof or other waterproof covering.

##### Touch-Up Paint Specifications:

- Touch-up paint is for installation use only.
- Touch-up paint is for professional use only.
- Touch-up paint should be used sparingly. (Example: Use to cover exposed nail heads, small nicks, or scratches less than one inch in length and less than 1/16" wide.)
- Do not apply to spots larger than 3/4" in diameter. If larger repair is required, replace the Insulated wall panel.
- Apply touch-up paint to all cut edges.
- Apply touch-up paint only when air, siding and paint temperature is above 50° F.
- Store touch-up paint at temperatures between 40° F and 100° F.
- Shake touch-up paint for 90 seconds before every use.
- Do not freeze touch-up paint. Do not use if you suspect touch-up paint has been frozen.
- Do not apply touch-up paint to SnapTight Products if wet.
- Avoid touch-up painting late in the day when dew is likely to form or when precipitation is possible.

#### **Care and Maintenance of SnapTight Products**

##### After Installation

- Periodic cleaning is recommended to remove dirt and dust that may build up over time. Rinse SnapTight Products Insulated Stucco Building Products with a garden hose using a low-pressure spray. Never use harsh or harmful chemicals that can damage SnapTight Products Insulated Stucco Building Products. Never use a high-pressure power washer or high-pressure nozzles.

