

1. Identification

Product identifier Thermacell Mosquito Mat

Other means of identification

SDS number 71910-2

Recommended use Mosquito repellent.

Recommended restrictions For outdoor use only.

Manufacturer/Importer/Supplier/Distributor information

Company name Thermacell Repellents, Inc.

Address 32 Crosby Drive
Bedford, MA 01730
United States of America

Website www.thermacell.com

Telephone +1-781 430-5277

Emergency telephone CHEMTREC: +1-703-527-3887
CCN 19760

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 1
Hazardous to the aquatic environment, long-term hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Not assigned.

Response Collect spillage.

Storage Not assigned.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Cellulose	9004-34-6	60 - 80
DL-3-allyl-2-methylcyclopent-2-en-4-one-1-yl	231937-89-6	10 - 30
DL-cis,trans-chrysanthemate		

Chemical name	CAS number	%
Distillates (petroleum), hydrotreated light	64742-47-8	7 - 13
6,6'-di-tert-Butyl-4,4'-diethyl-2,2'-methylenediphenol	88-24-4	1 - 5

Composition comments The exact concentrations of the materials in this product are withheld as a trade secret (29CFR1910.1210(i)) and are available to a physician or paramedical personnel in a emergency situation.
All concentrations are in percent by weight unless otherwise indicated.
Components not listed are either non-hazardous or are below reportable limits.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Do not induce vomiting. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical During fire, hazardous combustion products are released that may include: Carbon oxides. Nitrogen oxides

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do it without risk. Cool containers exposed to flames with water until well after the fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Avoid contact with eyes, skin, and clothing. Ensure adequate ventilation. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Recover and recycle, if practical. Avoid the generation of dusts during clean-up. Prevent product from entering drains. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water. Retain and dispose of contaminated wash water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Provide adequate ventilation. Avoid contact with skin, eyes and clothing. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Keep only in original packaging. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value
Cellulose (CAS 9004-34-6)	TWA	10 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Not normally needed. If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Rubber, neoprene or PVC. Other suitable gloves can be recommended by the glove supplier.

Skin protection

Other

Wear suitable protective clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Follow OSHA respirator regulations (29CFR 1910.134) and use NIOSH/MSHA approved respirators. Check with respiratory protective equipment suppliers.

Thermal hazards

No protection is ordinarily required under normal conditions of use.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Solid.

Color	Blue.
Odor	Characteristic.
Odor threshold	Property has not been measured.
pH	Not applicable (material is insoluble in water).
Melting point/freezing point	Property has not been measured.
Initial boiling point and boiling range	Property has not been measured.
Flash point	Property has not been measured.
Evaporation rate	Not applicable, material is a solid.
Flammability (solid, gas)	Will burn if involved in a fire.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Property has not been measured.
Explosive limit - upper (%)	Property has not been measured.
Vapor pressure	Not applicable, material is a solid.
Vapor density	Not applicable, material is a solid.
Relative density	Property has not been measured.
Solubility(ies)	
Solubility (water)	(< 0.1%) Insoluble in water.
Partition coefficient (n-octanol/water)	Not applicable, product is a mixture.
Auto-ignition temperature	Property has not been measured.
Decomposition temperature	Property has not been measured.
Viscosity	Not applicable, material is a solid.
Other information	
Density	4 lb/ft ³
Explosive properties	Not explosive.
Kinematic viscosity	Not applicable, material is a solid.
Oxidizing properties	Not oxidizing.
Particle size	Property has not been measured.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Decomposition is not expected under normal conditions of use and storage. For hazardous combustion products, see section 5.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be harmful if inhaled.
Skin contact	Prolonged skin contact may cause temporary irritation. Contains component(s) which may be absorbed through the skin.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity	May be harmful if inhaled.
-----------------------	----------------------------

Product	Species	Test Results
Thermacell Mosquito Mat (CAS Mixture)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 14 days
Inhalation		
LC50	Rat	> 8.48 mg/l
Oral		
LD50	Rat	> 2000 mg/kg, 14 days
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Corrosivity		
Thermacell Mosquito Mat		Primary skin irritation Result: Not irritating. Species: Rabbit
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity	Not listed.	
NTP Report on Carcinogens	Not listed.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological information		
Ecotoxicity	Very toxic to aquatic life with long lasting effects.	
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available on bioaccumulation.	
Mobility in soil	The product is insoluble in water. Expected to have low mobility in soil.	
Other adverse effects	No data available for this product.	
13. Disposal considerations		
Disposal instructions	Recover and recycle, if practical. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.	

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information**DOT**

UN number	UN3077
UN proper shipping name	Environmentally hazardous substances, solid, n.o.s. (DL-3-allyl-2-methylcyclopent-2-en-4-one-1-yl DL-cis,trans-chrysanthemate)
Transport hazard class(es)	
Class	9
Subsidiary hazard	-
Label(s)	9
Packing group	III
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	8, 146, 335, A112, B54, IB8, IP3, N20, T1, TP33
Packaging exceptions	155
Packaging non bulk	213
Packaging bulk	240

IATA

UN number	UN3077
UN proper shipping name	Environmentally hazardous substance, solid, n.o.s. (DL-3-allyl-2-methylcyclopent-2-en-4-one-1-yl DL-cis,trans-chrysanthemate)
Transport hazard class(es)	
Class	9
Subsidiary hazard	-
Label(s)	9
Packing group	III
Environmental hazards	Yes
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (DL-3-allyl-2-methylcyclopent-2-en-4-one-1-yl DL-cis,trans-chrysanthemate)
Transport hazard class(es)	
Class	9
Subsidiary hazard	-
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Distillates (petroleum), hydrotreated light Listed
(CAS 64742-47-8)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations**US. Massachusetts RTK - Substance List**

Cellulose (CAS 9004-34-6)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

US. New Jersey Worker and Community Right-to-Know Act

Cellulose (CAS 9004-34-6)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Cellulose (CAS 9004-34-6)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

US. Rhode Island RTK

Cellulose (CAS 9004-34-6)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	21-July-2021
Revision date	02-October-2024

Version #
NFPA ratings

02



Disclaimer

Thermacell Repellents, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

1. Identification

Product identifier	Thermacell Butane Cartridge
Other means of identification	
Product code	C-15
CAS number	68476-85-7
Recommended use	Gas cartridge.
Recommended restrictions	Use only per label directions.
Manufacturer/Importer/Supplier/Distributor information	
Company name	Thermacell Repellents, Inc.
Address	32 Crosby Drive Bedford, MA 01730 United States of America
Website	www.thermacell.com
Telephone	+1-781 430-5277
Emergency telephone	CHEMTREC: +1-703-527-3887 CCN 19760

2. Hazard(s) identification

Physical hazards	Flammable gases Gases under pressure	Category 1 Liquefied gas
Health hazards	Not classified.	
OSHA defined hazards	Simple asphyxiant	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable gas. Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only with adequate ventilation. Do not enter storage areas or confined spaces unless adequately ventilated.	
Response	Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.	
Storage	Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place.	
Disposal	Not assigned.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	Contact with liquefied gas may cause frostbite.	

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Petroleum gases, liquefied		68476-85-7	100

Constituents

Chemical name	Common name and synonyms	CAS number	%
n-Butane		106-97-8	≤ 60
Isobutane		75-28-5	≤ 40
Propane		74-98-6	≤ 1
1,3-Butadiene		106-99-0	< 0.1
Sulfur		7704-34-9	≤ 150 ppm

Composition comments Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory tract irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation. Get medical attention immediately.

Skin contact

Not likely, due to the form of the product. If frostbite occurs, immerse affected area in warm water (not exceeding 105°F/41°C). Keep immersed for 20 to 40 minutes. Get medical attention immediately.

Eye contact

Not likely, due to the form of the product. If frostbite occurs, immediately flush eyes with plenty of warm water (not exceeding 105°F/41°C) for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention promptly if symptoms persist or occur after washing.

Ingestion

This material is a gas under normal atmospheric conditions and ingestion is unlikely.

Most important symptoms/effects, acute and delayed

Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves. Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn").

Indication of immediate medical attention and special treatment needed

Exposure may aggravate pre-existing respiratory disorders. Provide general supportive measures and treat symptomatically.

General information

First aid personnel must be aware of own risk during rescue. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Extremely flammable gas. May form explosive mixtures with air. Gas may travel considerable distance to a source of ignition and flash back. During fire, hazardous combustion products are released that may include: Carbon dioxide.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Remove or isolate all sources of ignition. Do not extinguish a leaking gas fire unless leak can be stopped. Stop leak if you can do so without risk. Move containers from fire area if you can do so without risk. Do not direct water at source of leak or safety devices as icing may occur. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Extremely flammable gas. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. In the event of a leak evacuate all personnel until ventilation can restore oxygen concentrations to safe levels. No action shall be taken involving any personal risk or without suitable training. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat. Protect containers from damage. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not enter storage areas or confined spaces unless adequately ventilated. Use only outdoors or in a well-ventilated area. Oxygen concentration should not fall below 19.5 % at sea level (pO₂ = 135 mmHg). Mechanical ventilation or local exhaust ventilation may be required. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Material	Type	Value
Petroleum gases, liquefied (CAS 68476-85-7)	PEL	1800 mg/m ³
		1000 ppm

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Material	Type	Value
Petroleum gases, liquefied (CAS 68476-85-7)	IDLH	2000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Material	Type	Value
Petroleum gases, liquefied (CAS 68476-85-7)	TWA	1800 mg/m ³
		1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Applicable for industrial settings only.

Skin protection	
Hand protection	Wear protective gloves. Nitrile gloves are recommended. Use gloves with breakthrough time of 15 minutes. Minimum glove thickness 0.6 mm. Applicable for industrial settings only.
Skin protection	
Other	Wear suitable protective clothing. Applicable for industrial settings only.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. WARNING! Air-purifying respirators do not protect workers in oxygen deficient atmospheres. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. Follow OSHA respirator regulations (29CFR 1910.134) and use NIOSH/MSHA approved respirators. Check with respiratory protective equipment suppliers. Applicable for industrial settings only.
Thermal hazards	Contact with liquefied gas might cause frostbites, in some cases with tissue damage. Wear appropriate thermal protective clothing, when necessary. Applicable for industrial settings only.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Gas.
Form	Compressed liquefied gas.
Color	Colorless.
Odor	Faint disagreeable odor.
Odor threshold	Property has not been measured.
pH	Not applicable (material is insoluble in water).
Melting point/freezing point	< -292 °F (< -180 °C)
Initial boiling point and boiling range	30.2 °F (-1 °C) (@ 1013 hPa)
Flash point	-40 °F (-40 °C)
Evaporation rate	Property has not been measured.
Flammability (solid, gas)	Extremely flammable gas.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	8.5 % (@ 1013 hPa)
Explosive limit - upper (%)	1.44 % (@ 1013 hPa)
Vapor pressure	345 kPa (80.6 °F (27 °C))
Vapor density	2 (Air=1) (59 °F (15 °C))
Relative density	Property has not been measured.
Solubility(ies)	
Solubility (water)	(< 0.1%) Insoluble in water.
Partition coefficient (n-octanol/water)	Property has not been measured.
Auto-ignition temperature	770 °F (410 °C) (@ 1013 hPa)
Decomposition temperature	Not applicable as the product is not unstable.
Viscosity	Not applicable for product form.

Other information

Density	563 kg/m ³ (Liquid phase)
Explosive properties	Not explosive.
Kinematic viscosity	Not applicable for product form.
Molecular formula	UVCB
Oxidizing properties	Not oxidizing.
Particle size	Not applicable for product form.

10. Stability and reactivity

Reactivity	Reacts violently with strong oxidants, nitrites, inorganic chlorides, chlorites and perchlorates causing fire and explosion hazard.
Chemical stability	Stable under normal temperature conditions and recommended use.
Possibility of hazardous reactions	May form explosive mixture with air.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Strong acids. Halogens. Nitrates. Nitrites. Chlorites. Inorganic chlorides. Perchlorates.
Hazardous decomposition products	Thermal decomposition of this product can generate carbon monoxide and carbon dioxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	High concentrations: Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Breathing of high concentrations may cause dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness.
Skin contact	Contact with liquefied gas may cause frostbite.
Eye contact	Contact with liquefied gas may cause frostbite.
Ingestion	This material is a gas under normal atmospheric conditions and ingestion is unlikely.

Symptoms related to the physical, chemical and toxicological characteristics	Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves. Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn").
---	--

Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.
-----------------------	-----------------------------------

Toxicological data

Constituents	Species	Test Results
Propane (CAS 74-98-6)		
Acute		
Inhalation		
Gas		
LC50	Rat	> 80000 ppm, 15 Minutes
Skin corrosion/irritation	Not classified.	
Serious eye damage/eye irritation	Not classified.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
NTP Report on Carcinogens		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	

Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not relevant, due to the form of the product.
Chronic effects	Exposure over a long period of time may cause central nervous system effects.

12. Ecological information

Ecotoxicity	The product is not expected to be hazardous to the environment.
Persistence and degradability	Not relevant, due to the form of the product.
Bioaccumulative potential	Not relevant, due to the form of the product.
Mobility in soil	Not relevant, due to the form of the product.
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Use the container until empty. Do not dispose of any non-empty container. Empty containers have residual vapor that is flammable and explosive. Cylinders should be emptied and returned to a hazardous waste collection point. Do not puncture or incinerate even when empty. Dispose in accordance with all applicable regulations.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 °F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose in accordance with all applicable regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN2037
UN proper shipping name	Receptacles, small, containing gas or gas cartridges (flammable), without release device, not refillable
Transport hazard class(es)	
Class	2.1
Subsidiary hazard	-
Label(s)	2.1
Packing group	-
Environmental hazards	
Marine pollutant	No
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Shipped as Limited Quantity per 49 CFR § 173.306.
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	None
IATA	
UN number	UN2037
UN proper shipping name	Receptacles, small, containing gas or gas cartridges (flammable), without release device, not refillable
Transport hazard class(es)	
Class	2.1
Subsidiary hazard	-
Label(s)	2.1
Packing group	-
Environmental hazards	No
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Containers less than 1 kg shipped as Limited Quantity.

IMDG

UN number	UN2037
UN proper shipping name	RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES) without a release device, non refillable
Transport hazard class(es)	
Class	2
Subsidiary hazard	-
Packing group	-
Environmental hazards	
Marine pollutant	No
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Exempt from classification under Special Provision 191.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) This substance is on the TSCA 8(b) inventory and is designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Gas under pressure
Simple asphyxiant

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Petroleum gases, liquefied (CAS 68476-85-7)

US. New Jersey Worker and Community Right-to-Know Act

Petroleum gases, liquefied (CAS 68476-85-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Petroleum gases, liquefied (CAS 68476-85-7)

US. Rhode Island RTK

Petroleum gases, liquefied (CAS 68476-85-7)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	15-June-2021
Revision date	02-October-2024
Version #	02
NFPA ratings	



Disclaimer

Thermacell Repellents, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.