



by Schneider Electric

List Price \$1,227.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

Service Disconnect - 2P Circuits (max.)	1
Branch Circuit Breaker - Ampere Rating (max.)	100A
Hub Type	A
Branch Circuit Breaker - Spaces	8
Branch Circuit Breaker - Tandems (max.)	8
Branch Circuit Breaker - Circuits (max.)	16
Wire Size - Line Side Main Lugs	#6 to 350 AWG/kcmil (Al/Cu)
Wire Size - Service Ground Lug	#12 to #2/0 AWG (Al/Cu)
Ampere Rating	100A
Short Circuit Current Rating	22kA
Mounting Style	Surface mount or convertible to semi-flush with appropriate flange kit
Service (Type of Feed)	OH/UG
Bypass Type	horn bypass
Style	Ringless type
Feed-Thru Lugs	Yes
Service Disconnect - Type	QOM2100VH (factory installed)
Service Disconnect - Maximum Ampere Rating	100A
Application	Combination Service Entrance Device (CSED)
Approvals	ANSI Certified, UL Listed
Depth	35.13 Inches
Enclosure Rating	NEMA 3R
Height	4.67 Inches
Indoor/Outdoor	Outdoor
Maximum Single Pole Circuits	16
Number of Jaws	5
Number of Sockets	1
Phase	1-Phase
Spaces	8
Voltage Rating	120/240 VAC
Width	14.37 Inches

Shipping and Ordering

Category	00048 - Meter Mains, Type HOM
Discount Schedule	DE3A
GTIN	00785901401827
Package Quantity	1
Weight	42.9 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y

Generated: 06/16/2016 16:26:47

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.