

## Model WT52 UL Listed Wire Combinations Strip Wires 1/2 in.

UL File Number E5238

Copper to Copper wire only (do not use on aluminum)



For use with solid or stranded combinations

600 Volt Maximum			
2 to 3 #10	1 #10 w/1 #12	1 #12 w/1 to 5 #16	1 #14 w/2 to 5 #16
2 to 5 #12	1 #8 w/1 #10, #12, or #14	1 #12 w/1 to 4 #14	2 #14 w/1 to 4 #18 or #16
2 to 6 #14	1 #10 w/2 to 5 #18	1 #12 w/1 #14 and 1 to 4 #16	3 #14 w/1 to 3 #16
4 to 6 #16	1 #10 w/1 to 4 #16	1 #12 w/2 #14 and 1 or 2 #16	4 #14 w/1 or 2 #18
6 #18	1 #10 w/1 or 2 #14 or #12	2 #12 w/3 or 4 #18	4 #14 w/1 #16
1 #12 w/5 #14	1 #10 w/1 #14 and 1 to 3 #16	2 #12 w/1 to 3 #16	5 #14 w/1 #18
1 #12 w/4 #16 or #14	1 #10 w/2 #14 and 1 #16	2 #12 w/1 to 3 #14	1 #16 w/4 or 5 #18
1 #12 w/2 #14	1 #10 w/1 #12 and 1 #14	2 #12 w/1 #14 and 1 or 2 #16	2 #16 w/2 to 4 #18
1 #12 w/1 #14	1 #10 w/1 #12 and 1 or 2 #16	3 #12 w/1 or 2 #16	3 #16 w/1 to 3 #18
1 #10 w/3 #14	2 #10 w/1 or 2 #16	3 #12 w/2 #18	4 #16 w/1 or 2 #18
1 #10 w/4 #14	2 #10 w/1 #14	1 #14 w/3 to 5 #18	5 #16 w/1 #18
1 #10 w/2 #14	1 #12 w/2 to 5 #18	1 #14 w/3 #12	