

CLEAR

CLEAR



Kwik Seal Plus®

Premium Adhesive Sealant

MOLD GUARD
TECHNOLOGY

**Fights the Growth of Stain &
Odor-Causing Mold & Mildew
on the Sealant**

- **100% Waterproof**
- **Crack Proof Guarantee**
- **Paintable**
- **Easy Water Clean-up
& Low Odor**

Kitchen, Bath & Plumbing

Read back panel for cautions!
¡Lea las precauciones en el panel posterior!

5.5 fl oz (162 mL)

DAP® KWIK SEAL PLUS® Premium Kitchen & Bath Adhesive Sealant contains MoldGuard Antimicrobial Product Protection to fight the growth of stain & odor causing bacteria, mold & mildew on the sealant. The sealant is easier to clean & stays cleaner between cleanings. Provides excellent flexibility & adhesion for durable, 100% waterproof seal. Paintable.

FOR BEST RESULTS: Apply in temperatures above 40°F. Not for continuous underwater use. Joint width should not exceed 3/8". If joint depth exceeds 3/8", use foam backer rod. Sealant applies white & dries clear in 7-14 days (depending on joint depth, temperature & humidity). Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Remove cap & cut nozzle at 45° angle to desired bead size. 3. Squeeze sealant into gap or crack. 4. Smooth bead before sealant skins over. 5. Clean excess dried sealant with damp sponge before it skins over. Dried sealant must be cut or scraped away. 6. **PAINTABLE.** Allow sealant to dry clear before painting with latex or oil-based paints. 7. Wait 18 hours before exposing to water or moisture. 8. Reseal tube for storage & reuse.

COVERAGE: 30 linear ft at 3/16" diameter bead

CAUTION! Contains texanol. May cause mild skin irritation. Do not get in eye, on skin, or on clothing. Use gloves and safety glasses. Use in well-ventilated area. Do not ingest. **FIRST AID:** SKIN: Wash thoroughly. EYE: Immediately flood with large quantities of water. **INHALATION:** Remove to fresh air. **INGESTION: DO NOT INDUCE VOMITING.** Get medical attention immediately if complications arise from exposure. **For emergencies,** call your poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN. ¡PRECAUCIÓN!** Contiene texanol. Puede irritar levemente la piel. Evite el contacto con los ojos, la piel o la ropa. Use guantes y gafas de seguridad. Use en un área bien ventilada. No ingiera. **PRIMEROS AUXILIOS:** PIEL: Lávese muy bien. OJOS: Lávese con abundante agua. **INHALACIÓN:** Salir al aire fresco. **INGESTIÓN: NO INDUZCA EL VÓMITO.** Busque atención médica si surgen complicaciones debido a la exposición. **En caso de emergencia,** llame a un centro de control de envenenamiento al 800-222-1222. Para más información, consulte la Hoja de datos de seguridad (SDS). Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ WARNING Cancer and Reproductive Harm / **ADVERTENCIA** Cáncer y Daños al Sistema Reproductor - www.P65warnings.ca.gov

NCCS Calif. ARB VOC <1.5% wt/wt (32.2 g/L)

CRACK PROOF GUARANTEE: DAP warrants that this product will not mildew, crack, peel or separate, when used as directed within one year of purchase. If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be liable responsible for incidental or consequential damages.

QUESTIONS? ¿PREGUNTAS? Call/Llame al 888-DAP-TIPS or visit/o visite dap.com & click on/ y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al 888-327-8477 o visite dap.com.

© DAP Products Inc.
Baltimore, MD 21224

Made in the USA with U.S. and globally sourced materials
dap.com

