

WHITE

WHITE

WHITE

WHITE



Contains: Phthalate esters & trimethoxyvinylsilane. During application & cure, methanol is released. Use only with adequate ventilation. Avoid breathing vapors. Ensure fresh air entry during application & drying. Harmful if swallowed. May cause allergic skin reaction & sensitization. Avoid contact with eyes & skin. Do not ingest. Wear rubber gloves and eye protection. **FIRST AID: SKIN:** Wash skin thoroughly with soap & water. Do not use solvents or abrasive cleansers to remove from skin. **EYES:** Immediately flood with large quantities of water. **INGESTION: DO NOT INDUCE VOMITING.** For emergencies, call poison control center at 800-222-1222. See SDS for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

Contiene: Esteres de ftalato y viniltrimetoxisilano. Durante la aplicación y el curado, se libera metanol. Utilice solamente con ventilación adecuada. Evite inhalar las emanaciones. Proporcionar aire fresco, durante la aplicación y el secado del producto. Dañino si se ingiere o se absorbe a través de la piel. Podría causar sensibilización alérgica en la piel. Evite el contacto con los ojos y la piel. No lo ingiere. Use guantes y utilice protección para los ojos con protectores laterales. **PRIMEROS AUXILIOS: PIEL:** Lave cuidadosamente. **OJOS:** Enjuague con grandes cantidades de agua. **INGESTION: NO INDUZCA EL VOMITO.** Para emergencias, llame al centro de control de envenenamiento al 800-222-1222. Refiérase a la SDS para más información. Para una SDS contacte su proveedor o visite dap.com. **MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ WARNING Cancer & Reproductive Harm / ADVERTENCIA Cáncer y Daños al Sistema Reproductivo –
www.P65warnings.ca.gov

Para obtener las instrucciones y garantía en español, llame al 888-DAP-TIPS o visite dap.com.

QUESTIONS/¿PREGUNTAS?
Call/Llame al 888-DAP-TIPS or visit/o visite dap.com & click on/ y pulse en "Ask the Expert."

DAP Global Inc.
Baltimore, MD 21224
Made in the USA with U.S. and globally sourced materials.
dap.com

AMP™

ADVANCED MODIFIED POLYMER

ALL WEATHER SEALANT

HYBRID TECHNOLOGY

MAXIMUM PERFORMANCE

OUTPERFORMS SILICONE:



WET SURFACE APPLICATION



30 MINUTE PAINT READY



CRYSTAL CLEAR CLARITY

**STAYS FLEXIBLE
UV RESISTANT**

**0-140°F
TEMP RANGE**

**30 MIN.
RAIN READY**

LIFETIME GUARANTEE

Window, Door Siding & Trim

WARNING! MAY CAUSE EYE & SKIN IRRITATION.

Read back panel carefully for other cautions.

¡ADVERTENCIA! PUEDE IRRITAR LOS OJOS Y LA PIEL.

Lea atentamente el panel posterior para otras precauciones.

9.0 FL OZ (266 mL)

DAP® AMP™ Advanced Modified Polymer All Weather Window, Door & Siding Sealant provides a 100% weatherproof & waterproof seal with the ability to be applied on wet & damp surfaces. It has a fast 30 minute paint & rain ready time & is specially formulated to meet ASTM C920, Class 35. Exterior/Interior.

ADHERES TO:

Wood – painted & unpainted, Vinyl, Most plastics, Aluminum, Most metals, Fiber cement, Concrete, Natural stone, Brick, Glass, Ceramic, Fiberglass, Stucco, Most common building materials

SPECIFICATIONS

ASTM C920, Class 35

PHYSICAL PROPERTIES

App. Temp Range:	0°F to 140°F
Ideal Bead Size:	3/16" (recommended)
Coverage:	49 lin. ft at 3/16" dia. bead
Skin Time:	30 minutes
Tack Free Time:	2 hours
Full Cure Time:	24 hours
Paint Ready Time:	30 minutes
Rain Ready Time:	30 minutes
Flexibility:	Permanently flexible
Mold Resistance:	Cured sealant is mold & mildew resistant
Odor:	Very mild
Clean-Up:	Mineral spirits
Shelf Life:	12 months (unopened/cool & dry conditions)

VOC CCCS Calif. ARB VOC <3 wt/wt% (9.9 g/L)

* Superior color and clarity over traditional clears but may discolor under certain conditions.

FOR BEST RESULTS: Application temp range: 0°F to 140°F. Not for continuous underwater use. Joint width should not exceed 1/2". If joint depth exceeds 1/2", use foam backer rod.

INSTRUCTIONS: 1. Surface must be clean, structurally sound and free of all foreign material. 2. Trim nozzle at 45° angle between 1/8" and 3/16" mark. 3. Completely puncture inner foil seal for best flow rate. 4. Load cartridge into caulk gun. 5. Apply consistent 3/16" bead size for optimal joint protection. If necessary, tool or smooth the bead of sealant with a finishing tool before the sealant skins over. 6. Allow to cure for at least 30 minutes before exposing to water. Sealant may still be tacky. Sealant reaches full performance in 24 hours. 7. Paintable in 30 minutes. Use high quality acrylic latex coatings. 8. Clean up excess uncured sealant with mineral spirits. Cured sealant must be cut or scraped away. DO NOT use mineral spirits or any other solvent to clean skin. 9. Reseal cartridge for storage and reuse. Store product below 80°F & away from moisture.

LIFETIME GUARANTEE DAP warrants this product for sealant purposes during the lifetime of your home, when used as directed, within one year of purchase. Call 888-DAP-TIPS, with your sales receipt and product container available for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.