



INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 50 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

153 x 15 motor is designed for optimal performance with this fan. Fan is Energy Star Rated. 220 VAC, 50 Hz export version available.

BLADES:

A set of five 20.7" traditional all-weather composite blades is included.

CONTROL OPTIONS:

Optional CW1, CW1SW, CW2, CW5 and CWRL4 wall controls and CRL4WH and CRL8TS remote controls (with receiver units) are available—sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

Optional lighting fitters and light kits are available. See our catalog or visit www.fanimation.com for available lighting options.

DOWNROD OPTIONS:

Dual mount for flush mount application or 1" dia x 4.5" long downrod. Optional downrods available in 12", 18", 24", 36", 48", 60", and 72" lengths. A downrod coupler is available for installations requiring a downrod longer than 72". Fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 6 " downrod. Call technical support for more information.

LOCATION USE:

Fans are rated for dry and damp locations.

Available Finishes				
Fan / Housing Assembly Blades - Traditional				
MW – Matte white	Matte white composite blade			
OB – Oil-rubbed bronze	Walnut composite blade			
SN – Satin nickel	Cherry composite blade			

Fan w/60" downrod

Fan w/72" downrod

68.70"

80.70"

66.60"

78.60"

Airflow / Energy Efficiency Info (120V)						
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts	
High	188	5897	92	0.53	64	
Med	124	3701	128	0.37	29	
Low	65	1744	174	0.21	10	