

CARE AND MAINTENANCE

- Cleaning and maintenance of the shower wall panels should be performed on a regular basis.
- The ideal cleaning time is right after shower use. Soap scum, lime and other heavy soil could contain invasive materials. The lack of cleaning and maintenance could result in damaging the surface of the wall panels and the core. Lack of cleaning shower walls could create discoloration of the wall panel.
- Shower walls should be cleaned regularly with a nonabrasive all purpose household cleaner or window cleaner. Always test your cleaning solution on an inconspicuous area before applying to the entire surface.
- Avoid using abrasive cleaners, scouring powders, grit, acid, acetone, alkaline and ammonia.
- To extend the life span of the wall panels, daily cleaning with wet wipes and proper diluted neutral detergent (PH 7-8) is recommended. Always clean with wet cloth as dry cleaning could scratch the surface.
- Avoid high concentrations of solvents, strong alkaline and strong acidic solution during the cleaning process.
- A thin layer of wax could be applied to the surface of wall panel after cleaning process.
- Improper use of tools and sharp objects will create permanent scratch damage on the surface.

■ **QUESTIONS? PLEASE CONTACT:**

CUSTOMER SERVICE:

CALL: 888.620.3667 OR FAX: 219.947.3630

customerservice.us@FGI-Industries.com

CRAFT + MAIN®

www.craftandmain.com