

Features

- Four-sided water containment with full-length threshold guard and weep channels for added protection.
- Low 3-inch profile for easy entry and exit.
- Durable high gloss finish.
- 48" (1220 mm) x 34" (864 mm) x 3-1/8" (79 mm) base finished dimensions.

Material

Compression molded from our exclusive Vikrell® material.

Installation

 Suitable for tile down application or with STERLING STORE+™ wall surround.



GUARD+[™]

48" Shower Base





Codes/Standards

CSA B45.5/IAPMO Z124 Greenguard UL 2818 - Gold

STERLING[®] Warranty - Fixtures Made of Solid Vikrell Material

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color Code Description

\bigcirc	0	White
\bigcirc	96	Biscuit





Technical Information

All product dimensions are nominal.		
Installation:	3-Wall Alcove	
Drain location:	Center	
Drain hole diameter:	3-5/16" (84 mm)	
Weight:	30 lbs (13.6 kg)	
Minimum flat for door:	2-1/2" (64 mm)	
Door width required:	47" (1194 mm)	

Notes

Install this product according to the installation instructions.

GUARD+[™]

48" Shower Base

Studs should be positioned roughly as shown.

Double studding is recommended for pivot shower door installations.