


Installation Guide

Atlas STAINLESS STEEL MICRO-MESH
Gutter Guard


Start Here For A Typical Installation

This guide covers typical installations. For more information on other install scenarios, please scan the QR code located on the front of the install guide.

1 Clean Out Your Gutters



2 Measure & Cut Gutter Guard as Needed



Use a new, or freshly sharpened, pair of tin snips to cut through the aluminum rail and mesh.

3 Determine the Slope of Your Roof

The optimum slope for gutter guard install is 5-25°.


Option 1



Standard Roof

If your roof looks like this, continue to **OPTION 1**.

Option 2




Steeply Pitched Roof

If your roof looks like this, continue to **OPTION 2**.

4 Start Laying First Section

We recommend starting at an inside corner. If you don't have one, start at the downspout.

Option 1 Standard Roof Installation




Carefully slide the rear rail of the gutter guard under the roof shingles. Continue to step 5.

IMPORTANT: If your roofing material is adhered to your underlayment, do not use this method. Use the bending method demonstrated in Option 2.


OR

CONTINUE TO OPTION 2 →


Option 2 Below the Roofline Installation



MEASURE & MARK: Measure the length from the lip of the gutter to the fascia board. Using that measurement, mark a line on the gutter guard where you will bend the mesh.




CLAMP MESH: Clamp the gutter guard between two 1"x2" boards to hold it in place.




BEND THE MESH: Use the leverage from the clamp and/or boards to bend the mesh along the line you've marked.

Note: Bend the mesh either up or down depending on your gutter-to-roof scenario.



INSTALL GUARDS: Screw the mesh to the fascia board using 3 screws per section. Continue to step 5.

5 Screw to Attach



SCREW IT DOWN: Use the guides on the front rail to place the screw. Fasten with 3 screws for each section.

Installation Guide

STAINLESS STEEL MICRO-MESH





NEED HELP?

atlasgutterguard.com/contact
844.359.7683
M-F 8am-7pm CST

DO NOT RETURN THIS PRODUCT TO THE STORE!
Please contact our Customer Experience Team at (844) 359-7683. We likely will be able to resolve the issue.

Safety Is Our #1 Priority.

During installation we recommend that you...

- Wear gloves and safety glasses.
- Use an extension ladder and standoff for stability.
- Make all cuts and bends to the gutter guards on the ground.

ALSO MAKE SURE TO:

- Obey local building codes.
- Check to see if your roofing material is adhered to your underlayment. Do not pry up your shingles or tear your underlayment. Find alternate methods by scanning the QR code on the front cover.
- Remove any labels/stickers from the gutter guard piece as needed.

FREEZING CONDITIONS

If you live in an area that is prone to freezing, the following issues can occur with any gutter guard:


Icicles & Ice Dams

Icicles and ice dams may form on your gutter during freezing conditions. Ice dams can cause water to leak back into your home. Icicles can break and cause serious bodily harm and injury. Properly installed, operated and maintained heating elements on your roof and gutter can melt icicles and ice dams. Use a local licensed electrical contractor in good standing for installing any heating element products.

Snow Melting

Snow melt may result in water runoff from your roof which can refreeze on the ground below creating a potential slipping hazard.


HOW-TO Inside Corners



Register Today

Register your gutter guards for our 30 year warranty!

BONUS OFFER




FREE GIFT

Register your product for our 30 year warranty and get a FREE gutter guard brush.

www.atlasgutterguard.com/register


*Shipping and handling not included.

HOW-TO Outside Corners



Lay one end of the mesh so it overlaps directly over the other section. Note: The rear rail has more exposed mesh than the front rail. This is intentional.

HOW-TO End Caps



Installation Resources



atlasgutterguard.com/install