


Light and mirror Mirror with lighting # LM7827D0000 / LM7827D00006000

|< 39 3/8" Inch >|



| Mirror with lighting | Dimension | Weight | Order number |
|---|---|---|-----------------|
| Premium-Version, cEGS/IAPMO®*, LED ambient light (4 sided), LED dimming function, 1 sensor switch bottom right, de-fogging system with Auto-Off function, mirrors require a GFCI 110 V 60 Hz power source, flat plug will be supplied with mirror, LED (life span > 30,000 hours), LED module permanently enclosed, LED module 4000 kelvin light color, 52 Watt | ı | | |
| Colors | | | |
| 00 White | | | |
| Variant | | | |
| | 39 3/8" x 1 1/4" I | nch | LM7827D0000 |
| | 39 3/8" x 1 1/4" l | nch | LM7827D00006000 |
| Infobox | | | |
| # LM 7825D, LM 7826D, LM 7827D and LM 7828D are available surfaces = minimum 3", Sensor controls both light and heater, * CSA C22.2 No. 12-1982 | from stock, Distand * Complies with foll | ce between sensor and re owing standards: UL 962 | flecting and |
| | | | |
| | | | |

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.