

INSTALLATION INSTRUCTION FOR 5171

For Wall Mount Light Fixtures

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DUDISJONCTEUR.

READ AND SAVE THESE INSTRUCTIONS

PREPARATION

1. Shut off the power at the fuse box or circuit breaker. If necessary, remove the old fixture, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any parts necessary for installation.

MOUNTING THE FIXTURE (Fig.1)

3. Secure hanging bracket (A) to junction box with junction box screws (B) (Size: #8-32*0.6"L). The side of the hanging bracket (A) marked "GND" must face out.

CONNECTING THE WIRES (Fig. 2)

4. Connect the fixture wires to the junction box wires as shown in Fig. 2. Make sure all wire connectors are secure. If there is no green ground wire from the junction box, connect the fixture ground wire to the hanging bracket (A) with the green screw provided. Tuck these wire connections neatly into the wall junction box.

COMPLETING THE INSTALLATION

5. Secure mounting backplate (D) to hanging bracket (A) with mounting screws (C) (Size: #8-32*0.3"L).
6. Place glass (F) over socket (E) and secure with socket ring (G) using wrench (H).
7. Install (1) one medium base bulbs (I) up to 100 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification.

DO NOT EXCEED THE SPECIFIED WATTAGE!
(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

Return the power to the junction box and test the fixture. Your installation is now complete.

