

TIPS

- **IMPORTANT:** Shake well before and frequently during spraying
- Cover surrounding areas to protect from over spray
- Dispense a quick burst on scrap material to activate pressure
- Practice spraying on scrap material before applying
- Spray using intermittent bursts

FEATURES & BENEFITS

- Excellent texture match
- 30 Minute paint ready time depending on temperature, humidity & amount applied
- Sag-resistant formula
- White texture - no priming required
- Low odor
- Easy water clean-up

INSTRUCTIONS

SAFETY FIRST! PRODUCT IS EXTREMELY FLAMMABLE WHEN DISPENSING. Before using, read and understand all health and safety/product use instructions. Always point spray tip down and away from people.

SURFACE PREPARATION: Surface must be clean, dry, structurally sound and free of all foreign material. Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.



- 1 SHAKE** can upside down vigorously for more than a minute after hearing mixing marble moving freely in the can.
- 2 INSERT STRAW** attachment into tip of actuator. **IMPORTANT:** Dispense a quick burst of material on scrap materials to activate pressure and practice distance to the ceiling and spray pattern before applying to surface. Shake frequently during use.
- 3 SPRAY** by placing finger on designated indentation at the base of the actuator, holding can approximately 12 inches away from ceiling. **DO NOT SPRAY** directly above you. Spray using intermittent bursts. For optimal blending, use different stroke motions or a circular pattern. Apply texture in overlapping passes to avoid gaps or uneven spots. If not satisfied, scrape off and reapply. **IMPORTANT:** Be sure that the area is well ventilated and proper safety gear is worn.
- 4 PAINT:** Allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior applications, use an exterior grade paint.
- 5 CLEAN-UP** straw, nozzle, tools, and area with towel and warm water. Invert can pointing the top straight down. Spray a quick burst onto a trash can until texture is cleared from outlet. Remove any texture build-up from the actuator tip.
- 6 STORE** at room temperature, avoid extreme cold or heat.



POP CORN

CEILING TEXTURE
Textura para techo

 **WATER-BASED**
LOW ODOR • EASY CLEAN-UP

EXCELLENT TEXTURE MATCH



**STRONG
ADHESION**
Sag-Resistant Formula

**TEXTURE & PRIME
IN ONE STEP**
Easy Application

PRO RESULTS
FROM THE #1 WALL REPAIR BRAND*

**DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE
FLASH FIRE. IRRITANT. CONTENTS UNDER PRESSURE.**
Read back panel carefully for cautions.

**¡PELIGRO! EXTREMADAMENTE INFLAMABLE.
LOS VAPORES PUEDEN CAUSAR COMBUSTIÓN ESPONTÁNEA.**
Leer el panel posterior cuidadosamente para las advertencias.

Contains crystalline silica, calcium carbonate and dimethyl ether. May irritate eye, skin and lung. May cause sensitization by inhalation or skin contact. Individuals with lung or breathing problems such as asthma must not be exposed to vapor. Use only with adequate ventilation. Do not breathe vapor. Ensure fresh air entry during application and drying. Avoid contact with skin & eyes. Wear protective clothing, protective gloves & eye protection. Vapor may ignite explosively. Keep away from heat, sparks & flame. Do not smoke. Extinguish all flames & pilot lights. Turn off stoves, heaters, electrical motors, & other sources of ignition during use & until vapor is gone. Do not puncture, strike or incinerate can. Do not expose to heat or store at temperature above 120°F. Harmful if swallowed. Do not ingest. **FIRST AID:** SKIN: Wash thoroughly with soap and water. EYE: Remove immediately with a clean dry rag. Get medical attention. INHALATION: Remove to fresh air. INGESTION: **DO NOT INDUCE VOMITING.** Get medical attention immediately. **For emergencies, call your Poison Control Center at 800-222-1222. See Safety Data Sheet (SDS) at dap.com for additional information. KEEP OUT OF REACH OF CHILDREN.**

Contiene sílice cristalina, carbonato de calcio y éter dimetilico. Puede irritar los ojos, la piel y los pulmones. Puede causar sensibilización por inhalación o contacto con la piel. Utilicelo solamente con ventilación adecuada. No respire el vapor. Garantice la entrada de aire fresco durante la aplicación y el curado. Evite el contacto con la piel y los ojos. Use ropa y guantes protectores y protección para los ojos. El vapor se puede encender explosivamente. Manténgalo alejado del calor, chispas y llamas. No fume. Apague todas las llamas, incluso las llamas del piloto. Apague las estufas, calentadores, motores eléctricos y otras fuentes de ignición durante el uso y hasta que el vapor se haya disipado. No perforo, golpee ni incinere la lata. No exponga al calor ni almacene a temperaturas superiores a 49°C (120°F). Nocivo si se traga. No lo ingiera. **PRIMEROS AUXILIOS:** PIEL: Lávese muy bien con agua y jabón. OJOS: Retire inmediatamente con un paño limpio y seco. Obtenga atención médica. INHALACIÓN: Lleve hacia el aire fresco. INGESTIÓN: NO INDUZCA EL VÓMITO. Obtenga atención médica de inmediato. **Para emergencias llame a su Centro de control de envenenamientos al 800-222-1222. Consulte la Hoja de datos de seguridad (SDS) en dap.com para más información. MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

**⚠ WARNING Cancer / ADVERTENCIA Cáncer –
www.P65Warnings.ca.gov**

VOC: <15 wt/wt% (222g/L)

LIMITED WARRANTY: If product fails to perform when used as directed within one year of date of purchase, call 888-DAP-TIPS with your sales receipt and product container available, for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.

*Based on independent hardware and lumber channel dollar sales in the Wall Repair category.

QUESTIONS? / ¿PREGUNTAS? Call/Llame al 888-DAP-TIPS or visit/o visite dap.com & click on/y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en