SQR31103LA

X Series 2.5A 3 Speed Slide Fan Controller Back Wires Matte Light Almond

Green Premium™ Product

Main

Range	Square D X Series
Product or Component Type	Fan controller
Device Application	Control
Device presentation	Mechanism with fixing frame
Aesthetic name	X Series
Actuator	Slide

Complementary

Number of gangs	1 gang
Number of poles	1
Switch Function	1-way
[Ie] rated operational current AC	2.5 A
[Ue] rated operational voltage	120 V
Network type	AC
Network Frequency	60 Hz
Load type	Fan motor
Maximum Horse Power Rating	0.25 hp
Load current	2.5 A
Mounting Mode	By screws
Device mounting	Flush
Material	Plastic strap Metal fixing frame
Color	Light almond
Surface Finish	Matt
Width	1.89 in (48 mm)
Height	4.06 in (103 mm)
Depth	2.52 in (64 mm)
Quantity per Set	1 piece

Environment

Product Certifications	cULus
Standards	UL 1917

Ordering and shipping details

Category	09932 - WD BASIC DEVICES
Discount Schedule	DE9
GTIN	785901535058
Nbr. of units in pkg.	1
Package weight(Lbs)	4.23 oz (120 g)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.17 in (10.6 cm)
Package 1 width	2.44 in (6.2 cm)
Package 1 Length	2.56 in (6.5 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	1920
Package 2 Weight	663.18 lb(US) (300.811 kg)
Package 2 Height	47.24 in (120 cm)
Package 2 width	39.37 in (100 cm)
Package 2 Length	47.24 in (120 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: carbon black, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	1 year