

Project:			
Fixture Type:			
Location:			
Contact:			

Z-1070 LED

Wall vertical only Mounted • Wet Location Listed PROGRESS LED

Description:

Z-1070 LED Collection Black Two-Light Large LED Outdoor Sconce

Specifications:

- · White Acrylic Diffuser
- · Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 4.75 in W., 20.875 in ht., 0.5625 in depth
- · Mounting backplate for outlet box included
- \cdot 6 in of wire supplied
- · Americans With Disabilities Act (ADA) compliant

Performance:

Number of Modules	2		
Input Power	11 W		
Input Voltage	120 V		
Input Frequency	60 Hz		
Lumens/LPW (Delivered)	1,019/46 (LM-79)		
ССТ	3000 K		
CRI	90 CRI		
Life (hours)	54000 (L70/TM-21)		
EMI/RFI	FCC Title 47, Part 15, Class B		
Warranty	5-year Limited Warranty		
Labels	cCSAus Wet Location Listed		
	Meets California Title 24 JA8-2019		


P560209-031-30



Dimensions:

Width: 6 in Depth: 3-3/4 in Height: 23-1/8 in H/CTR: 11-9/16 in

White Acrylic Diffuser Width: 4-7/16 in Height: 22-9/16 in





Z-1070 LED

Wall vertical only Mounted • Wet Location Listed PROGRESS LED

P560209-031-30

Dimming Notes:

P560209-031-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Leviton_IPI06-1LZ

Leviton_SureSlide 6674

Lutron_Nova T VTELV-300

Lutron_Diva DVELV-300P

Lutron_Ariadni AYCL-153P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.