

MINERAL SEALER

Material Safety Data Sheet - MSDS



Manufacturer / distributor information:

Vasari Lime Plaster & Paint llc

115 North Olive St.

Ventura, CA, 93001

Telephone: (805) 667-8454

Prepared July 24, 2019 by Vasari Lime Plaster & Paint LLC

website: www.vasariplaster.com

24 hour emergency – Chemtrec 1-800-424-9300

I. Identification and Product Names

Product Names: Mineral Sealer

Trade Names: Plaster Sealer, Tadelakt Sealer, Stucco Sealer

Product used for interior and / or exterior wall finishes.

II. Chemical Composition

Vasari LLC products as listed above are composed of the following materials:

Components not listed are either non-hazardous or are below the reportable limits.

III. Hazards Identification

Physical hazards Not classified.

Health hazards Carcinogenicity Non classified

OSHA defined hazards Not classified.

Hazard statement Not classified.

Precautionary statement

Prevention Observe good industrial hygiene standards

Disposal Dispose of wasyer and residues in accordancewith local authority requirements.

Storage Store away from incompatible materials.

Response if exposed or concerned: Wash wands after handling

Hazard(s) not otherwise classified (HNOC) None known.

Ingestion:

Rinse mouth. Get medical attention if irritation persists.

Eye Contact:

Rinse with water. Get medical attention if irritation persists.

Skin Contact:

Rinse with water. Get medical attention if irritation persists. Direct contact with eyes

Chronic Exposure: Seek medical attention if irritation persists.

Aggravation of Pre-existing Conditions: Direct contact with eyes may cause temporary irritation.

IV. First Aid Measures for Accidental Exposure: DANGER! HARMFUL IF SWALLOWED OR INHALED.

Skin Exposure:

Rinse with water. Get medical attention if irritation persists. Direct contact with eyes

Eye Contact:

Rinse with water. Get medical attention if irritation persists.

Inhalation:

Move to fresh air. If not breathing, get medical attention if irritation persists.

Ingestion:

DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Call a physician immediately.

Chronic Exposure: Seek medical professional

Aggravation of Pre-existing Conditions: Seek medical professional

V. Fire Fighting Measures

Fire rating for interior application over drywall

Flash Point: Noncombustible solid

Upper/Lower Explosive Limits: N/A

Special Fire Fighting Procedures: None

Explosion: Not considered to be an explosion hazard.

VI. Accidental Release Measures

Cleanup and Disposal of Spill:

Contain spilled material in the most convenient and safe manner. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations.

VII. Handling and Storage

Handling:

Some products are in over 50 lbs. 5 gallon containers. Use appropriate care in lifting / handling heavy materials.

Storage:

Keep package tightly closed and at room temperature. Mineral Sealer has no shelf life.

VIII. Exposure Controls / Personal Protection

Exposure Guidelines:

Due to the encapsulated form of these products, no exposure to the components in the products is anticipated under normal use conditions.

Engineering Controls:

Ventilation must be adequate to maintain the ambient workplace atmosphere below OSHA exposure limit(s).

Respiratory Protection:

Follow the OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN 149. Always use a NIOSH/MSA approved respirator when necessary.

Eye / Face Protection:

Wear safety glasses with side shields or goggles.

Skin Protection:

Wear latex gloves and protective clothing to minimize skin contact.

Occupational exposure limits:

No exposure limits noted for ingredients.

IX. Physical and Chemical Properties

Physical Appearance: clear / white liquid

Odor: Mild Odor

pH: 10.1

Specific Gravity: ND

Water Solubility: Dilutable in water.

Melting Point: ND

Freezing Point 32°F

Boiling Point: 212°F

Vapor Pressure: equal to water

Vapor Density: Equal to water

Percent Volatiles by Volume: @ 21C (70F): 30-40

VOC Content: This product contains zero (0) Volatile Organic Compounds.

Viscosity: ND

X. Stability and Reactivity

Chemical Stability:

Stable and non reactive

Conditions to Avoid:

Protect from freezing and excessive heat

Materials / Chemicals to Be Avoided:

ND

Hazardous Decomposition Products:

ND

Hazardous Polymerization: ND

XI. Toxicological Information

Carcinogenicity: ND

Acute Eye Irritation:

May cause temporary irritation

Acute Skin Irritation:

May cause temporary irritation

Acute Respiratory Irritation:

No adverse affects.

Acute Oral Toxicity:

May cause gastrointestinal irritation if swallowed

Chronic Toxicity:

May cause irritation to the eyes.

Effects of Dust Overexposure: ND

Inhalation: No adverse affects.

Dermal Exposure: Not absorbed through the skin. No adverse affects.

Eye Irritation: May be irritating to the eyes, with burning, itching, or redness.

Carcinogenicity: This product is not a carcinogen by IARC, ACGIH, NTP or OSHA

Ingestion: Not considered a likely route of exposure.

PRECAUTIONS FOR SAFE HANDLING AND USE

Special care should be take to prevent dust from becoming airborne. The use of ventilation and wet methods are recommended.

Respiratory Protection:

Non required

XII. Ecological Information

Ecotoxicological Information:

This products in not classified as environmentally hazardous.

Environmental Fate: This material is not expected to significantly bioaccumulate.

Environmental Toxicity: No information found. No adverse affects.

XIII. Disposal Considerations

Waste Disposal Method:

Dispose of in accordance with federal, state and local regulations. Recycle all paper bags, plastic pales and lids in appropriate recycling facilities.

Mineral Sealer can be disposed in a sink with no environmental affects.

XIV. Transportation Information

Freight Class: 50

Handling unit: 5 gallon and 2 gallon pail.

US Department of Transportation	Proper Shipping Name	None
Shipping Name: US Department of Transportation	None	
Hazard Class	None	
ID Number	None	
Packaging Group	None	

XV. Regulatory information US federal regulations

TSCA: The components of this mixture are listed or are exempt from listing in the Toxic Substance Control Act Inventory of Chemical Substances. This product does not contain any chemicals that would require export notification under Section 12(b) of the TSCA regulation.

This product contains no: Cadmium (Cd), Chromium (Cr), Lead (Pb), Tin (Sn), nor any organic elements that can cause cancer. This product contains no ozone-depleting compounds

XVI. Other information

Date of preparation or last revision Issue date

July 24, 2019, 2017

Vasari Plaster & Stucco provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. Vasari Plaster & Stucco

MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, Vasari Plaster & Stucco WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by:
Product Safety
Vasari Lime Plaster & Paint
115 North North Olive St.
Ventura, CA 93001