# INSTALLATION INSTRUCTIONS FOR P5546-66A-L For LED Flush Mount READ AND SAVE THESE INSTRUCTIONS

## WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER AVERTISSEMENT!COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DO DISJONCTEU

#### ASSEMBLING THE FIXTURE (Fig.1)

- 1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
- Position mounting plate (A) on the ceiling and mark the location of three drywall anchors (D). Pre-drill holes for drywall anchors (D). Then insert drywall anchors (D) into the ceiling.
- Attach mounting plate (A) to junction box (not included) using mounting screws (B) (Size: 8-32\*1/2"L). The side of mounting plate (A) marked "GND" must face out.
- Place wood screws (E) through the holes of mounting plate (A) and into drywall anchors (D) to secure mounting plate (A) to the ceiling.

### CONNECTING THE WIRES (Fig.2)

 Connect the electrical wires as shown in Fig.2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to mounting plate (A) using green screw (C) provided.

#### COMPLETING THE INSTALLATION

switches.

- 7. Align canopy (F) onto mounting plate (A) and secure with screws (G).
- 8. Adjust LED disc (H) to desired angle.

Your installation is now complete. Return power to the junction box and test the fixture.

**CAUTION /ATTENTION**: When handling fixture, do not apply pressure to LEDs. Hold fixture by the base only.

IMPORTANT: Fixture should be installed by a qualified electrician to ensure proper wiring and installation. Dimmable with ELV and/or LED compatible wall dimmer





