



CAULKS & SEALANTS / TAPES



For more Information scan the QR Code
www.greatstuff.com

MULTI-PURPOSE TECHNICAL DATA SHEET

CLEAR - 99ALLP3000 / WHITE - 99ALLP3001 / BLACK - 99ALLP3002
GRAY - 99ALLP3003 / SANDSTONE - 99ALLP3030

PRODUCT DESCRIPTION

GREAT STUFF™ Multi-purpose Silicone is a moisture-curing, 100% RTV acetoxysilicone sealant. High in strength and exceptional in flexibility, this versatile sealant is perfect for a wide range of home improvement and new construction tasks. It is ideal for sealing exterior windows, doors, siding, trim, molding, vents, as well as spaces in basements and attics. Additionally, it is suitable for sealing sinks, showers, bathtubs, toilets, kitchen countertops, exterior gutters, sheds, RVs, and around wire and pipe chases.

PROPERTIES

- 100% Acetoxysilicone RTV Silicone Sealant Caulk
- Reusable nozzle with cap
- Interior & Exterior
- 12 minute set time / 30 minute dry time
- Strong adhesion and durability
- Low odor
- Mildew resistant
- UV resistant
- Lifetime Product Warranty
- Non-paintable



Non Paintable



For Interior & Exterior Use



UV Resistant

GREAT STUFF™ is a trademark or registered trademark of affiliates of DuPont de Nemours, Inc. used under license by National Adhesive Inc.

NATIONAL ADHESIVE INC.

8280 WILLOW OAKS CORPORATE DRIVE, SUITE 600, FAIRFAX, VA 22031, U.S.A
+1 (855) 674-4583 | greatstuff@nationaladhesive.com | www.nationaladhesive.com





CAULKS & SEALANTS / TAPES



For more Information scan the QR Code
www.greatstuff.com

MULTI-PURPOSE

TECHNICAL DATA SHEET

TECHNICAL INFORMATION

Chemical Base:	Acetoxy silicone
Specific gravity:	1.02 ± 0.03 gr/cm ³
Tack free time (77°F/25°C and 50% R.H):	12 Minutes
Cure Rate (1 day) (77°F/25°C and 50% R.H):	0.08 inch/2mm
Modulus at 100% (MPa):	≈0.3 Mpa
Tensile Strength:	≈1.50 Mpa
Elongation at Break:	> 500%
Shore Hardness:	15 ± 3 Shore A

APPLICATION DETAILS

Application Temperature:	41°F to 104°F (5°C to 40°C)
Temperature Resistance:	-40°F to 302°F (-40°C to 150°C)

- For best results, the surface must be clean, dry and free of dust, oil and grease, to ensure a clean and strong adherence between the sealant and the surface.
- Cut off the cartridge tip, screw on the removable nozzle and cut tip to your desired bead size.
- Insert cartridge into caulking dispenser.
- Hold at a 45° angle and apply ahead of nozzle to achieve a smooth seal.
- Sealant normally dries to touch in 30 minutes and cures & bonds on average 24 hours.
- Uncured product can be cleaned with a solvent.
- Once cured, the product can be removed mechanically.

COLORS

Clear, White, Black, Gray & Sandstone

GREAT STUFF™ is a trademark or registered trademark of affiliates of DuPont de Nemours, Inc. used under license by National Adhesive Inc.

NATIONAL ADHESIVE INC.

8280 WILLOW OAKS CORPORATE DRIVE, SUITE 600, FAIRFAX, VA 22031, U.S.A
+1 (855) 674-4583 | greatstuff@nationaladhesive.com | www.nationaladhesive.com





CAULKS & SEALANTS / TAPES



For more Information scan the QR Code
www.greatstuff.com

MULTI-PURPOSE

TECHNICAL DATA SHEET

SHELF LIFE

- 15 months from manufactured date when unopened.
- Store the product in a cool and dry place.
- Do not store in extreme cold, direct sunlight, and temperatures above 122°F/50°C.

CAUTION

Avoid contact with eyes and skin. Do not breathe vapors. Do not take internally. In case of eye contact, flush thoroughly with water. In case of skin contact, flush thoroughly with water. If breathed in, move person into fresh air. If swallowed, do not induce vomiting. Call a physician immediately.

HEALTH AND SAFETY

For more information, please refer to the most recent Safety Data Sheet found at www.greatstuff.com.

GREAT STUFF™ is a trademark or registered trademark of affiliates of DuPont de Nemours, Inc. used under license by National Adhesive Inc.

NATIONAL ADHESIVE INC.

8280 WILLOW OAKS CORPORATE DRIVE, SUITE 600, FAIRFAX, VA 22031, U.S.A
+1 (855) 674-4583 | greatstuff@nationaladhesive.com | www.nationaladhesive.com

