

TEST REPORT



REPORT NO.: CTNT2503250010101R

Product name: Wide-Spread Bathroom Faucet

Model No.: BF001

Applicant: Popin Trading Co. Limited

Test procedure: Entrustment Test

Shenzhen CTNT Testing Technology Co., Ltd.



TEST REPORT

Appendix S to Subpart B of Part 430—Uniform Test Method for Measuring the Water Consumption of Faucets and Showerheads

Report Number.....: CTNT2503250010101R

Date of issue.....: Apr.08,2025

Name of Testing Laboratory preparing the Report.....: Shenzhen CTNT Testing Technology Co., Ltd.
Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China
Tel: 086-755-28680489
E-mail: admin@ctnt-cert.com
Web: www.ctnt-cert.com

Applicant's name.....: Popin Trading Co. Limited

Address.....: Unit 1101B, Lippo Sun Plaza 28 Canton Road, Tsim Sha Tsui, Kowloon Hong Kong

Test specification:

Standard.....: 10 CFR 430, Appendix S of Subpart B.
10 CFR 430.32

Test procedure.....: 10 CFR 430, Appendix S of Subpart B.

Non-standard test method.....: N/A

Test Report Form No.....: DOE- SLT-TRF

Test Report Form(s) Originator.....: 1.0

Master TRF.....: CTNT

General disclaimer:

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing CTNT Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the CTNT, responsible for this Test Report.

Test item description.....: Wide-Spread Bathroom Faucet

Model/Type reference.....: BF001

Trade Mark.....: TETOTE

Manufacturer.....: Popin Trading Co. Limited

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com

Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
Laboratory Name:	Shenzhen CTNT Testing Technology Co., Ltd.	
Testing location/ address:	Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China	
Tested by(Test Engineer):	Schale Zeng	<i>Schale Zeng</i>
Reviewed By(Supervisor):	Oliver Long	<i>Oliver Long</i>
Approved by(Chief Engineer):	Flight Lee	<i>Flight Lee</i>
Summary of testing:		
Tests performed (name of test and test clause): Determination of the result includes consideration of measurement uncertainty from the test equipment and methods. A representative sample of the product covered by this report has been tested and pipe fittings complies with the requirements of 10 CFR 430, Appendix S of Subpart B.	Testing location: Shenzhen CTNT Testing Technology Co., Ltd. Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China Tel: 086-755-28680489 E-mail: admin@ctnt-cert.com Web: www.ctnt-cert.com	
General conditions for measurements:		
<p>1. General Test Set-up Conditions</p> <p>1.1 Flow rate test Procedure(According to the standard ASME A112.18.1-2012 / CSA B125.1-2012)</p> <p>1.1.1) Fittings shall be tested at the maximum flow setting, if adjustable, with both hot and cold water valves fully open on combination fittings. The flow rate test shall be conducted with water between 5 and 71°C(40 and 160F) in accordance with the intended end use of the fitting and under the following conditions: (a) for minimum flow: at 140+7kPa (20+1nsi) at the inlet when water is flowing: and (b) for maximum flow for faucets: at 410±7kPa (60±1 psi) at the inlet when water is flowing.</p> <p>1.1.2) Flow rate tests for shower heads, body sprays, and hand showers shall be conducted with water at 38±6°C(100±10F) and the flow maintained for at least 1 min. The flow rate test for (a) maximum flow for shower heads shall be conducted at 550±14kPa (80±2psi); (b) minimum flow for shower heads and hand showers shall be conducted at 310±14kPa (45±2 psi). If the shower head or hand-held shower has more than one mode, the minimum flow rate shall be determined at a flowing pressure of 310±7kPa (45±1 psi) in all modes. Pause or trickle modes designed to flow at less than 1.9 L/min (0.5gpm) at 550kPa (80 psi) shall be excluded from the minimum flow requirements; and Note: The intent of Item(b) is to aid in the selection of an appropriate automatic compensating valve. (c) high-efficiency shower heads and hand-held showers shall be conducted in accordance with Clause</p>		

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com

Possible test case verdicts:
- test case does not apply to the test object.....: N/A
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)
Declared data for Device:
Maximum Flow Rate.....(gpm): 1.01 gpm
Testing:
Sample arrival date.....: Mar.25,2025
Test period.....: Apr.08,2025
General remarks:
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a <input type="checkbox"/> comma / <input checked="" type="checkbox"/> point is used as the decimal separator. Clause numbers between brackets refer to clauses in 10 CFR 430.32.
Remark:
- All tests are carried out on BF001.
Other important notes:
<ol style="list-style-type: none"> 1. If you have any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receipt of the report. 2. Entrusting test only responsible for the incoming samples, and the test results are used by the entrusting party to understand the quality of the samples. 3. This test report is invalid without the "test stamp". 4. This report may not be reproduced in part without permission to avoid ambiguous interpretation. 5. Test items with "*" by to subcontract. 6. The remaining samples under test must be collected within three months of receipt of the inspection report. If the samples are not collected within the time limit, the laboratory will handle them by selves. <p>Company name: Shenzhen CTNT Testing Technology Co., Ltd. Address: Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China Tel: 086-755-28680489 Email: admin@cntn-cert.com</p>

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@cntn-cert.com

Web: www.ctnt-cert.com

§ 430.32	Energy and water conservation standards and their compliance dates.		P	
(o)	Faucets.		P	
	The maximum water use allowed for any of the following faucets manufactured after January 1, 1994, when measured at a flowing water pressure of 60 pounds per square inch (414 kilopascals), shall be as follows:		P	
	Faucet type	Maximum flow rate (gpm (L/min)) or (gal/cycle (L/cycle))	P	
	Lavatory faucets	2.2 gpm (8.3 L/min) ^{1 2}	1.01 gpm	P
	Lavatory replacement aerators	2.2 gpm (8.3 L/min)		N/A
	Kitchen faucets	2.2 gpm (8.3 L/min)		N/A
	Kitchen replacement aerators	2.2 gpm (8.3 L/min)		N/A
	Metering faucets	0.25 gal/cycle (0.95 L/cycle) ^{3 4}		N/A
(p)	Showerheads.		N/A	
	The maximum water use allowed for any showerheads manufactured after January 1, 1994, shall be 2.5 gallons per minute (9.5 liters per minute) when measured at a flowing pressure of 80 pounds per square inch gage (552 kilopascals). When used as a component of any such showerhead, the flow-restricting insert shall be mechanically retained at the point of manufacture such that a force of 8.0 pounds force (36 Newtons) or more is required to remove the flow-restricting insert, except that this requirement shall not apply to showerheads for which removal of the flow-restricting insert would cause water to leak significantly from areas other than the spray face.		N/A	

Summary of Test Results				
Model: BF001				
Item	Limited	Measured		Verdict
		Sample 1	Sample 2	
Flow Rate at 60 +/- 1 psi - Gallons perMinute	2.2 gpm	1.01 gpm	1.00 gpm	P
Average water flow		1.01 gpm		

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com

Photo Document



Photo 1: Sample appearance



Photo 2: Sample appearance

---END OF REPORT---

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com