



SBC15NCF



34.25" x 15" x 22.5" (H x W x D)

15" wide, built-in, commercially listed nitro coffee kegerator, auto defrost with digital thermostat, stainless steel door, front lock, black cabinet, sealed back, and includes all equipment necessary to dispense nitro coffee

Highlights:

15" wide design makes it ideal for smaller residential and commercial settings

Commercially approved tap kit includes all equipment to serve nitro coffee

Listed to NSF-7 standards and meets UL 471 for commercial use

Product Features:

| | |
|---|--|
| 15" wide design | Slim-fit design complements smaller commercial and residential spaces |
| Commercially approved | ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings |
| Built-in capability | Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require an extra ¼" of space due to the door design. For more information, see the user manual |
| Complete tap kit for serving nitro coffee | Commercially approved tap kit includes a stainless steel tower, Nitrogen tank, and regulator |
| Nitrogen tank included | 5 lb. Nitrogen tank included (ships empty) |
| Nitro coffee dispenser | 2.9 cu.ft. interior can accept a 1/6 (sixel) nitro coffee keg |
| Automatic defrost | Reduced user maintenance with auto defrost operation |
| Digital thermostat | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit |
| Tap cool system | Keeps cold air flowing to the tower for consistently cold nitro coffee |



SBC15NCF Specifications:

| Overview | |
|----------------------------|-------------------|
| Height of Cabinet | 34.25" (87 cm) |
| Width | 15.0" (38 cm) |
| Width with Door Open | 15.25" (39 cm) |
| Depth | 22.5" (57 cm) |
| Depth with Handle | 24.5" (62 cm) |
| Depth with door at 90° | 36.5" (93 cm) |
| Capacity | 2.9 cu.ft. (82 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Energy Usage/Year | 280.0kWh/year |
| Amps | 1.25 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 78.0 lbs. (35 kg) |
| Shipping Weight | 95.0 lbs. (43 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101067919 |
| Kegeerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Tap Kit | Yes |
| Height with Tap | 49.75" (126 cm) |
| Number of Taps | 1 |
| Adjustable Shelves | Yes |
| Shelf Type | Chrome |
| Shelf Qty | 2 |
| Thermostat Type | Digital |
| Fan Type | Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 1.06 oz. |
| High Side PSI | 150.0 |
| Low Side PSI | 50.0 |
| Inter Height | 26.75" (68 cm) |
| Interior Width | 11.75" (30 cm) |

| | |
|------------------------|----------------|
| Interior Depth | 17.5" (44 cm) |
| Compressor Step Height | 3.75" (10 cm) |
| Compressor Step Width | 11.75" (30 cm) |
| Compressor Step Depth | 5.0" (13 cm) |
| Level Legs Qty | 4 |
| Wheel Qty | 4 |
| Temperature Range | 34° to 50° F |

