

Physical Properties

Appearance Black thick paste	Drying Time @ 50% R.H. 68°F (20°C) 1 hr to touch	Maximum VOS 0.83 lbs/gal
Application Temperature 50°F and rising	Flash Point >212° F.	Solids By Weight 84%
Brookfield Viscosity 40,000 cPs @ 20 rpm	Freezability Do not freeze	Specific Gravity @ 77° F (25°C) 1.25
Color Black	Maximum VOC 50 g/l	Weight Per Gallon 10.2 - 10.6 lbs

Description

Features:

- Most durable crack repair
- Won't crack or shrink
- Easy-to-use application and clean-up

Usage

- Filling and sealing cracks up to 1/2" (12.7 mm) wide on asphalt pavements such as driveways and walks
- Repairing cracks before topcoating surface with all types of driveway sealers

Coverage

15 lineal feet of 3/8" bead per 10.1 oz. cartridge

Surface Preparation

Before application, cracks should be free of any loose materials, grass or weeds. Remove weeds and kill roots with weed killer. If crack is deep (more than 1" [2.5 cm]), fill crack with clean sand to within 1" (2.5 cm) of surface. For best results, crack should be damp, but free of standing water.

Application

DO NOT THIN. To prepare cartridge for application, trim tip to desired thickness of bead. Punch a large hole in the seal at end of spout and place in cradle-type caulking gun. Squeeze trigger slowly forcing filler into cracks and fill to ground level.

Precautions

Apply when temperature is at least 50°F (10°C) and when rain or frost is not likely within 24 hours. Allow filler to dry at least 24 hours in good weather before topcoating surface.

Cleanup

Clean tools with **Henry Scrubbers™ Hand & Tool Cleaning Towels** or kerosene, paint thinner or mineral spirits. Clean hands with **Henry Scrubbers™** or with waterless hand cleaner.

Caution

CAUTION! Close container after each use. **DO NOT TAKE INTERNALLY!** Use protective measures to avoid contact with eyes and skin. If swallowed, **CALL PHYSICIAN IMMEDIATELY!** In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. **GET MEDICAL ATTENTION!** Dispose of container and unused contents in accordance with Local, State and Federal regulations.

KEEP OUT OF REACH OF CHILDREN!

KEEP FROM FREEZING!

Warning: This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

10.1 / 10.3/ 11 OZ (1.17 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**