


FISCHBACH ARTWORK SPECIFICATIONS

MAXIMUM TEXT & GRAPHICS WIDTH 146MM



Clear

sticks to **WET** surfaces

The Tough Elastic Sealant for Every Job

Lexel®

Sticks to Almost Anything*

Instantly waterproof • Cured sealant is mildew resistant • Paintable

↑ **PUNCTURE ME HERE** ↑

USE ON:

showers • tubs • sinks • tile • countertops
backsplashes • cables • sills • drywall
windows • doors • moulding • trim
skylights • siding • wallpaper
thresholds • shingles • vents
ductwork • HVAC • eaves • gutters
flashing • pavers • retaining walls
endless possibilities!

***STICKS TO:**

itself • acrylic • copper • steel • aluminum
chrome • metal • nylon • fiberglass
terra-cotta • Plexiglas® • PVC
most plastics • ABS • polycarbonate
brick • polystyrene (not foam) • tile
porcelain • parquet • asphalt
masonry • Formica® • Lexan® • stone
glass • vinyl • canvas • paint • concrete
wood • fiber cement • & MORE!

DANGER: VAPOR HARMFUL.
FLAMMABLE. EYE & SKIN IRRITANT. Do not swallow. Do not breathe fumes. Do not use near heat, sparks or flames. Do not smoke. Do not get in eyes. Do not get on skin or clothing. **KEEP OUT OF REACH OF CHILDREN.** Wear safety glasses and chemical resistant gloves. Use only in a well-ventilated area.
Contains toluene.
FIRST AID: If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air.
WARNING: This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

VOC Content: 380g/L, 43% by wt.
Limited Lifetime Warranty: For a detailed description of the warranty & exclusions, visit www.sashco.com.

INSTRUCTIONS
Before you start:

- Apply to clean surfaces, free of frost, oil & dirt.
- Application range: 0°F to 120°F (-18°C to 49°C).
- Tack free in 30 minutes.
- Cures completely in 1 to 2 weeks.

Step 1. Cut tip to desired bead size, puncture inner foil seal, & apply.
Step 2. Use soapy water or mineral spirits to smooth out bead for best adhesion.
Step 3. Clean up with citrus-based cleaners or mineral spirits.

NOTE: Paintable in 48 hours with latex paints or in 7 days with oil-based paints. Not for use in areas of prolonged submersion.


INSTRUCCIONES
Antes de empezar:


- Aplicar sobre superficies limpias, libres de hielo, aceite y suciedad.
- Campo de aplicación: 0°F a 120°F (-18°C a 49°C).
- Tacto en 30 minutos.
- Cura completamente en 1 a 2 semanas.

Paso 1. Corte la boquilla hasta el tamaño deseado de la gota, agujerear el sello de aluminio, y aplique.
Paso 2. Para lograr mayor adhesión alise la gota con agua jabonosa o aceites minerales.
Paso 3. Limpie con detergentes cítricos o aceites minerales.

NOTA: Se puede pintar en 48 horas con pinturas de látex o en 7 días con pinturas de aceite. No debe utilizarse en zonas de inmersión prolongada.

DANGER
VAPOR HARMFUL.
FLAMMABLE. IRRITANT.
Read cautions on back label carefully.
10.5 FL. OZ. (310 mL)




©2017 Sashco, Inc.
10300 E. 107th Place
Brighton, CO 80601
800-767-5656
www.sashco.com
Made in the USA
Fabricado en los EE.UU.

CE
LXLCLCTG12-17

MAXIMUM GRAPHICS HEIGHT 185MM

MAXIMUM BAND WIDTH 155MM

 = White ink on a clear cartridge

10.5 FL. OZ. (310 mL)

Please send all links and images that are used within the file. If file is not converted to outlines, curves or paths, please send all fonts used within.