

# Oatey Great White Pipe Joint Compound Oatey Co.

Version No: 1.3.4.3

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **04/06/2021**Print Date: **06/04/2021**S.GHS.USA.EN

#### **SECTION 1 Identification**

#### **Product Identifier**

Product name	Oatey Great White Pipe Joint Compound
Chemical Name	Not Applicable
Synonyms	Not Available
Other means of identification	31229, 31230, 31231, 31232, 31233, 31234, 48007, 48008, 48009

# Recommended use of the chemical and restrictions on use

|--|

# Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Oatey Co.
Address	20600 Emerald Parkway, Cleveland, OH 44135 United States
Telephone	216-267-7100
Fax	Not Available
Website	<u>oatey.com</u>
Email	info@oatey.com

# **Emergency phone number**

Association / Organisation	hemtrec	
Emergency telephone numbers	1-800-424-9300 (Outside the US 1-703-527-3887)	
Other emergency telephone numbers	1-877-740-5015 (Emergency First Aid)	

# SECTION 2 Hazard(s) identification

# Classification of the substance or mixture

Classification	Not Applicable
----------------	----------------

# Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

# Hazard statement(s)

Not Applicable

 Version No: 1.3.4.3
 Page 2 of 12
 Issue Date: 04/06/2021

# **Oatey Great White Pipe Joint Compound**

Print Date: **06/04/2021** 

# Hazard(s) not otherwise classified

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. The thermal decomposition vapors of fluorinated polymers may cause polymer fume fever.

# Precautionary statement(s) Prevention

Not Applicable

# Precautionary statement(s) Response

Not Applicable

# Precautionary statement(s) Storage

Not Applicable

# Precautionary statement(s) Disposal

Not Applicable

# **SECTION 3 Composition / information on ingredients**

#### **Substances**

See section below for composition of Mixtures

#### **Mixtures**

CAS No	%[weight]	Name
1317-65-3*	30-50	calcium carbonate
64742-52-5*	30-40	Distillates (petroleum), hydrotreated heavy naphthenic
9002-84-0	5-15	<u>polytetrafluoroethylene</u>
13463-67-7*	5-10	<u>Titanium dioxide</u>
14808-60-7*	<=1	silica crystalline - quartz

# **SECTION 4 First-aid measures**

# Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

# Most important symptoms and effects, both acute and delayed

See Section 11

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 Fire-fighting measures**

# Extinguishing media

- ▶ Foam.
- ► Dry chemical powder.
- ► BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

 Version No: 1.3.4.3
 Page 3 of 12
 Issue Date: 04/06/2021

 Print Date: 06/04/2021
 Print Date: 06/04/2021

# Oatey Great White Pipe Joint Compound

# Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

# Special protective equipment and precautions for fire-fighters

Opeciai protective equipi	nent and precautions for me-lighters
Fire Fighting	<ul> <li>Alert Fire Department and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>Avoid spraying water onto liquid pools.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> </ul>
Fire/Explosion Hazard	Slight fire hazard when exposed to heat or flame.     Heating may cause expansion or decomposition leading to violent rupture of containers.     On combustion, may emit toxic fumes of carbon monoxide (CO).     May emit acrid smoke.     Mists containing combustible materials may be explosive. Combustion products include: carbon dioxide (CO2) hydrogen fluoride other pyrolysis products typical of burning organic material.

# **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

### **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

	▶ Clean up all spills immediately.
	Avoid breathing vapours and contact with skin and eyes.
Minor Spills	Control personal contact with the substance, by using protective equipment.
willor opins	<ul> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> </ul>
	▶ Wipe up.
	▶ Place in a suitable, labelled container for waste disposal.
	► Clear area of personnel and move upwind.
	Alert Fire Department and tell them location and nature of hazard.
	Wear breathing apparatus plus protective gloves.
	Prevent, by any means available, spillage from entering drains or water course.
	No smoking, naked lights or ignition sources.
	Fincrease ventilation.
Major Spills	Stop leak if safe to do so.
	Contain spill with sand, earth or vermiculite.
	<ul> <li>Collect recoverable product into labelled containers for recycling.</li> </ul>
	Absorb remaining product with sand, earth or vermiculite.
	<ul> <li>Collect solid residues and seal in labelled drums for disposal.</li> </ul>
	Wash area and prevent runoff into drains.
	If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# Precautions for safe handling

# Safe handling

- ▶ Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- ► Use in a well-ventilated area.
- ▶ Prevent concentration in hollows and sumps.

 Version No: 1.3.4.3
 Page 4 of 12
 Issue Date: 04/06/2021

 Print Date: 06/04/2021
 Print Date: 06/04/2021

#### **Oatey Great White Pipe Joint Compound**

▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ Avoid smoking, naked lights or ignition sources. ▶ Avoid contact with incompatible materials. ▶ When handling, **DO NOT** eat, drink or smoke. ▶ Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions. ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources. Other information ▶ Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

# Conditions for safe storage, including any incompatibilities

Suitable container	Metal can or drum     Packaging as recommended by manufacturer.     Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed.  For saturated perfluorocarbons:  Standard oxidation-reduction potentials do not apply to PFCs. The materials are unaffected by electrochemical reactions and do not dissociate in aqueous media.  They are essentially already fully oxidised and are unaffected by standard oxidizing agents such as permanganates, chromates, etc. The only known oxidation takes place only at high temperatures by thermal decomposition.  Likewise, the materials are only reduced under extreme conditions, requiring reducing agents such as elemental sodium  Avoid magnesium, aluminium and their alloys, brass and steel.  The most potentially reactive of this class, the perfluorinated tertiary amines and the quite analogous perfluorinated ethers, are similarly unreactive. Fluorinated tert-amines do not form salts or complexes with strong acids and are not attacked by most oxidizing or reducing agents

# SECTION 8 Exposure controls / personal protection

# Control parameters

# Occupational Exposure Limits (OEL)

# INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	calcium carbonate	Marble- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	calcium carbonate	Marble- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	calcium carbonate	Limestone- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	calcium carbonate	Calcium Carbonate- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	calcium carbonate	Limestone- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	calcium carbonate	Calcium Carbonate- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Marble - respirable	5 mg/m3	Not Available	Not Available	Not Available

 Version No: 1.3.4.3
 Page 5 of 12
 Issue Date: 04/06/2021

 Print Date: 06/04/2021
 Print Date: 06/04/2021

# **Oatey Great White Pipe Joint Compound**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Calcium carbonate - total	10 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Marble - total	10 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Limestone - total	10 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Limestone - respirable	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Calcium carbonate - respirable	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Distillates (petroleum), hydrotreated heavy naphthenic	Oil mist, mineral	5 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	Distillates (petroleum), hydrotreated heavy naphthenic	Mineral oil, excluding metal working fluids - Poorly and mildly Not Available refined		Not Available	Not Available	A2
US ACGIH Threshold Limit Values (TLV)	Distillates (petroleum), hydrotreated heavy naphthenic	Mineral oil, excluding metal working fluids - Pure, highly and severely refined (Inhalable particulate matter)	5 mg/m3	Not Available	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Titanium dioxide	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Titanium dioxide	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	Titanium dioxide	Titanium dioxide	Titanium dioxide 10 mg/m3		Not Available	(A4)
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO2+2) mg/m3 / 250 (%SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m3	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	silica crystalline - quartz	Silica, crystalline - α-quartz and cristobalite (Respirable particulate matter)	0.025 mg/m3	Not Available	Not Available	A2

# **Exposure controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

# Appropriate engineering controls

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

 Version No: 1.3.4.3
 Page 6 of 12
 Issue Date: 04/06/2021

 Print Date: 06/04/2021
 Print Date: 06/04/2021

#### **Oatey Great White Pipe Joint Compound**

and

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

#### Personal protection









# Eye and face protection

- Safety glasses with side shields
- ▶ Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

# Skin protection See Hand protection below Hands/feet protection Wear general protective gloves, eg. light weight rubber gloves. Body protection See Other protection below No special equipment needed when handling small quantities. OTHERWISE:

# Other protection

- Overalls.
- Barrier cream.
- ▶ Eyewash unit.

# Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

# **SECTION 9 Physical and chemical properties**

# Information on basic physical and chemical properties

Appearance	White Liquid Paste		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available

 Version No: 1.3.4.3
 Page 7 of 12
 Issue Date: 04/06/2021

 Print Date: 06/04/2021
 Print Date: 06/04/2021

# Oatey Great White Pipe Joint Compound

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	25000
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	> 100	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (%)	Not Available
Vapour density (Air = 1)	1.7	VOC g/L	3

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

# Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract. Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has <b>NOT</b> been classified as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence.
Skin Contact	The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis.
Eye	Although the liquid is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness (as with windburn).
Chronic	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.  Thermal decomposition vapors of fluorinated polymers may cause polymer fume fever.  In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that 'carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs.' (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Version No: 1.3.4.3 Page 8 of 12 Issue Date: 04/06/2021

# Oatey Great White Pipe Joint Compound

Print Date: 06/04/2021

# **SECTION 12 Ecological information**

# Toxicity

Oatey Great White Pipe	Endpoint		Test Duration (hr)		Species	Value	Value		Source	
Joint Compound	Not Available		Not Available		Not Available	Not Availab	e	Not Ava	ailable	
	Endpoint Test Duration (hr)			Species		Value		Source		
calcium carbonate	Not Available		Not Available		Not Available	Not Availab	e	Not Ava	ailable	
	Endpoint	Т	est Duration (hr)	Spe	ecies		Value		Source	
Distillates (petroleum),	ErC50	7	2h	Alg	ae or other aquatic p	lants	>1000	mg/l	1	
hydrotreated heavy	NOEC(ECx)	5	04h	Cru	stacea		>1mg/	l	1	
naphthenic	EC50	4	8h	Cru	stacea		>1000	mg/l	1	
	EC50	9	6h	Alg	ae or other aquatic p	lants	>1000	mg/l	1	
	Endpoint	dpoint Test Duration		n (hr) Species Value		Value	e Sourc		)	
polytetrafluoroethylene	Not Available		Not Available		Not Available	Not Availab	le	Not Ava	ailable	
	Endpoint	Test Duration (hr)		Spec	ies		Value		Source	
	EC50	72h		Algae	Algae or other aquatic plants		3.75-7.58mg/l		4	
	BCF	1008h		Fish		<1.1-9.6		7		
Titanium dioxide	EC50	48	Bh	Crustacea		1.9mg/l		2		
	LC50	96	Sh	Fish			1.85-3.06mg/l		4	
	NOEC(ECx)	50	)4h	Crustacea			0.02mg/l		4	
	EC50	96	6h	Algae	e or other aquatic pla	nts	179.05mg	ı/I	2	
	Endpoint		Test Duration (hr)		Species	Value		Source	<b>)</b>	
ilica crystalline - quartz	Not Available		Not Available		Not Available	Not Availab	le	Not Ava	ailable	
Legend:			ID Toxicity Data 2. Eu (QSAR) - Aquatic Tox		•		-			

Vendor Data

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
polytetrafluoroethylene	HIGH	HIGH
Titanium dioxide	HIGH	HIGH

# Bioaccumulative potential

Ingredient	Bioaccumulation	
polytetrafluoroethylene	LOW (LogKOW = 1.2142)	
Titanium dioxide	LOW (BCF = 10)	

# Mobility in soil

Ingredient	Mobility
polytetrafluoroethylene	LOW (KOC = 106.8)
Titanium dioxide	LOW (KOC = 23.74)

 Version No: 1.3.4.3
 Page 9 of 12
 Issue Date: 04/06/2021

 Print Date: 06/04/2021
 Print Date: 06/04/2021

# **Oatey Great White Pipe Joint Compound**

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- Reuse
- ▶ Recycling
- Disposal (if all else fails)

# Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- ▶ DO NOTallow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

# **SECTION 14 Transport information**

#### Labels Required

Marine Pollutant N

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
calcium carbonate	Not Available
Distillates (petroleum), hydrotreated heavy naphthenic	Not Available
polytetrafluoroethylene	Not Available
Titanium dioxide	Not Available
silica crystalline - quartz	Not Available

#### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
calcium carbonate	Not Available
Distillates (petroleum), hydrotreated heavy naphthenic	Not Available
polytetrafluoroethylene	Not Available
Titanium dioxide	Not Available
silica crystalline - quartz	Not Available

#### **SECTION 15 Regulatory information**

Safety, health and environmental regulations / legislation specific for the substance or mixture

 Version No: 1.3.4.3
 Page 10 of 12
 Issue Date: 04/06/2021

#### Oatey Great White Pipe Joint Compound

Print Date: 06/04/2021

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### Distillates (petroleum), hydrotreated heavy naphthenic is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### polytetrafluoroethylene is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### Titanium dioxide is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List International Agency for Research on Cancer (IARC) - Agents Classified by

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - California Proposition 65 - Carcinogens

the IARC Monographs

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes
US DOE Temporary Emergency Exposure Limits (TEELs)

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### silica crystalline - quartz is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### **Federal Regulations**

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	

 Version No: 1.3.4.3
 Page 11 of 12
 Issue Date: 04/06/2021

 Print Date: 06/04/2021
 Print Date: 06/04/2021

# **Oatey Great White Pipe Joint Compound**

Combustible Dust	No
Carcinogenicity	
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	
Aspiration Hazard	
Germ cell mutagenicity	
Simple Asphyxiant	
Hazards Not Otherwise Classified	

# US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

# **State Regulations**



#### US. California Proposition 65

WARNING: This product can expose you to chemicals including silica, crystalline, titanium dioxide, which is known to the State of California to cause cancer. For more information,go to www.P65Warnings.ca.gov.

# US - California Proposition 65 - Carcinogens: Listed substance

Titanium dioxide, silica crystalline - quartz

# **National Inventory Status**

National Inventory	Status
USA - TSCA	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory  No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

#### **SECTION 16 Other information**

Revision Date	04/06/2021
Initial Date	06/02/2021

# Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

 ${\sf PC-STEL} : {\sf Permissible\ Concentration-Short\ Term\ Exposure\ Limit}$ 

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

 Version No: 1.3.4.3
 Page 12 of 12
 Issue Date: 04/06/2021

 Print Date: 06/04/2021
 Print Date: 06/04/2021

# Oatey Great White Pipe Joint Compound

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances