

LED Wall Bracket

Wall mounted • Damp location listed **PROGRESS LED**

Description:

Beam LED vanity and sconces feature a squared, tubular opal glass diffuser paired with a simple, modern metal canopy. An integrated LED source provides a variety of energy and cost savings benefits. Suitable for residential and commercial applications.

Specifications:

- Polished Chrome (-015) (plated)
- Steel construction
- Etched Opal Glass Flat Square/Rectangular
- A tubular design pairs with a square back plate to create the Beam Collection, an LED fixture for bath and vanity areas
- 1-light 16-watt LED wall bracket
- Beam LED adds task lighting on either side or above a mirror to eliminate shadows on face when getting ready in the morning
- An integrated LED source provides a variety of energy and cost savings benefits for the homeowner
- Features a plated Polished Chrome finish
- Etched opal glass shade
- Measures 10 1/2"W x 4 3/4" H
- 62.5 lumens per watt
- Warm white 3000K lighting color, 1000 lumens and 90+CRI
- Adds task lighting on either side of mirror to eliminate shadows on face when getting ready in the morning
- Damp location listed
- Dimmable to 10% brightness (See Dimming Notes)
- Backplate covers a standard 4" octagonal recessed outlet box
- Mounting plate for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- Meets California Title 24 JA8-2016

Performance:

| | |
|---------------------|-------------------------------------|
| Number of Modules | 1 |
| Input Power | 16w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW | 1000/62.5 (LM-79) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | (L70/TM-21) |
| FCC | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp | -10 °C |
| Max. Operating Temp | |
| Warranty | 5-year limited warranty |
| Labels | cETLus Damp location listed |
| | Meets California Title 24 JA8-2016 |

P710049-015-30

Images:



Dimensions:

Width: 10-1/2"
Depth: 3-1/4"
Height: 4-3/4"
H/CTR: 8-3/8"

Glass
Height: 10"

P710049-015-30**Dimming Notes:**

P710049 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron - NTELV-300

Lutron - DVELV-300P

Lutron - DVCL-253P

Lutron - Caseta Wireless

Leviton – 6672

Leviton – 6674

Leviton - 6681

Lutron - AYCL-153P

Lutron - TGCL-153PH

Lutron - AYLTV-600P

Lutron - NTLV-600

Lutron - MAELV-601

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.