

# 6IN RECESSED SHALLOW Ceiling joists, or in suspended ceilings Mounted • Damp Location Listed

## Description:

6 Recessed Shallow Remodel Housing for 6" Trim

## Specifications:

- The housing and frame are constructed from die-formed corrosion resistant galvanized steel
- Its gasketed Air-Tight housing restricts airflow from conditioned spaces into unconditioned attic space, preventing unnecessary HVAC costs and improving the overall home energy efficiency
- An integral flange and locking springs create a snug fit against the ceiling, permitting quick mounting in 1/2 in. to 1-1/2 in. thick ceilings
- Wiring is made easy with the included wiring quick-connects that allow simple installation of 12-20 AWG wire without using separate wire nuts - simply strip supply wires and push in
- Use in conjunction with 6 in. shallow height remodel recessed housing
- Housing is provided with a medium base socket for a variety of bulbs - which are based on the trim used.
- The housing is compatible with a variety of trims and finishes to create different lighting effects or to easily match any decor
- CULus damp location rating makes this trim ideal for use in a variety of room settings and is thermally protected against improper use of lamps
- Fully dimmable with dimmable bulbs

## Performance:

Input Power	50 W
Input Voltage	120 VAC
Warranty	1-year Limited Warranty
Labels	cULus Damp Location Listed

## Compatible housing and lamp information:

TRIM	NON IC		IC	
	LAMP SHAPE	MAX WATTS	LAMP SHAPE	MAX WATTS
 P800020-028	BR30	50W	BR30	50W
	R30	50W	R30	50W
	PAR30	50W	PAR30	50W
 P806005-028	A19SBLED	10W	A19SBLED	10W
 P806004-028	A19SBLED	10W	A19SBLED	10W
 P806006-028 P806006-031	BR30	50W	BR30	50W
	R30	50W	R30	50W
	PAR30	50W	PAR30	50W
 P806007-028	BR30	50W	BR30	50W
	R30	50W	R30	50W
	PAR30	50W	PAR30	50W

# P806S-R-MD-ICAT



## Dimensions:

Length: 7-3/16 in  
 Width: 12-15/16 in  
 Height: 5-1/2 in

## Compatible LED trim information:

PAIR WITH THESE TRIMS	
	P800002-028-30
	P800018-028-CS
	P800019-028-CS
	HS56-WH-30K9
	P800021-028-30