# **Kate Sphere and Cone Pendant**

6592101, 6692101 1.0

# GENERATION LIGHTING

#### **Pendant**

#### **GENERAL PRODUCT INFORMATION:**

These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is safety listed for damp locations.

Incandescent version may be dimmed with a standard incandescent dimmer. LED version may be dimmed with a LED dimmer. Consult lamp manufacturer for additional information.

This instruction shows a typical installation.

#### **CAUTION - RISK OF FIRE**

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Use minimum 90°c supply conductors.

### GENERATION LIGHTING

7400 Linder Ave, Skokie, IL 160077 800.969.3347


# www.generationlighting.com

© 2020 Generation Lighting. All rights reserved. The "Generation Lighting" graphic is a registered trademark of Generation Lighting. Generation Lighting reserves the right to change specifications for product improvements without notification.



**SAVETHESE INSTRUCTIONS!** 

## Install the Fixture



- If necessary, screw the shorter end of the threaded nipple tightly onto the mounting plate and the screw collar onto the threaded nipple.
- 2 Secure the mounting plate to the junction box.
- 3 Determine the wanted height of the fixture and remove a portion of the chain by opening a link with pliers.
- Open the chain link with pliers and install the chain on the fixture loop, then re-close the chain link.
- Unscrew the collar nut from the screw collar, install the collar nut and the canopy onto the chain (in that order).
- Open a link on the other end of the chain with pliers and install the chain onto the screw collar to secure the fixture, re-close the link.
- Weave the cord through the chain, canopy, collar nut, screw collar, threaded nipple, and out of the junction box. Trim the cord leaving enough to make electrical connections.
- 8 Connect the fixture to a suitable ground in accordance to local electrical codes.
- 2 Connect the white fixture wire (square and/or rigid) to the neutral power line wire with a wire nut.
- Connect the black fixture wire (round and/or smooth) to the hot power line wire with a wire nut.
- Neatly place all the wires into the junction box, place the canopy onto the ceiling, and secure it in place by screwing the collar nut tightly onto the screw collar.
- Screw the lamp into the socket. Refer to the label on the socket for Max Wattage Information.
- Place the shade into the bracket and secure in place using the thumb screws.