

BLACK

BLACK

BLACK

BLACK

NEW
FormulaNEW
Formula

GUTTERS

FLASHING

ROOFS

SHINGLES

CHIMNEYS

ROOF

WATERPROOF
ASPHALT
SEALANT

- WET OR DRY SURFACE APPLICATION
- SEAL MINOR ROOF LEAKS, FILL GAPS & REPAIR LOOSE SHINGLES
- WILL NOT RUN OR BUBBLE
- EXCELLENT FLEXIBILITY & ADHESION

WARNING! COMBUSTIBLE
LIQUID AND VAPOR. READ BACK
PANEL CAREFULLY FOR OTHER CAUTIONS.
¡ADVERTENCIA! LIQUIDO
Y VAPOR COMBUSTIBLES.
LEA ATENTAMENTE LAS PRECAUCIONES
EN EL PANEL POSTERIOR.

10.1 FL. OZ. (300 mL)

DAP® ROOF Sealant is a high performance, asphalt-based sealant ideal for sealing minor roof leaks or repairing loose shingles. Offers excellent adhesive & weathering features. It resists cracking, crumbling & sagging for a 100% waterproof seal.

FOR BEST RESULTS: Apply in temps. above 40°F. Not for continuous underwater use. Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use backer foam rod. Tack free in 1 hour. Full cure in 2-4 weeks (depending on joint depth, temperature & humidity). Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface to be repaired must be free of loose, damaged asphalt & other foreign matter. 2. For wet surfaces, wipe off excess water. 3. Cut nozzle at a 45° angle to desired bead size. 4. Puncture inner foil seal. 5. Load cartridge into caulk gun. 6. Fill cracks & gaps with sealant. 7. Clean excess uncured sealant with mineral spirits. Excess cured sealant must be cut or scraped away. Do not use mineral spirits to clean skin. 8. Paintable after 1 hour with high-quality oil or asphalt-based paint. Two coats recommended. 9. Reseal cartridge for storage & reuse.

COVERAGE: 55 linear ft. at 3/16" diameter bead.

Contains mineral spirit and asphalt. May cause eye and respiratory tract irritation. May cause dizziness, headache or nausea. Harmful if inhaled or absorbed through skin. May cause skin irritation or burns. Do not breathe vapors. Use only in a well ventilated area. Ensure fresh air entry. Keep away from heat, sparks & flames. Do not smoke. Do not heat this product or apply to hot surfaces. Avoid eye & skin contact. Wear gloves & eye protection with side shields. Repeated & prolonged overexposure to solvents may cause kidney, liver, heart and permanent brain and nervous system damage. **FIRST AID:** SKIN: Wash thoroughly. EYE: Flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention immediately if complications arise from exposure. For emergencies, call poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.**

WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

NCCS CALIF. ARB VOC < 1.5% wt/wt.
(196 g/L)



WARRANTY: If product fails to perform when used as directed, within one year of date of purchase, call 1-888-DAP-TIPS with sales receipt & product container available, for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.

Contiene alcoholes minerales y asfalto. Puede causar irritación en los ojos y el sistema respiratorio. Puede causar mareos, dolor de cabeza o náuseas. Nocivo si se inhala o se absorbe a través de la piel. Puede causar irritación o quemaduras en la piel. No inhale las emanaciones. Use solo en un área bien ventilada. Cerciórese de que exista entrada de aire fresco. Manténgalo alejado del calor, las chispas y las llamas. No fume. No caliente este producto ni lo aplique en superficies calientes. Evite el contacto con los ojos y la piel. Utilice guantes y protección para los ojos que también posea protectores laterales. La sobreexposición repetida y prolongada a los solventes puede causar daños en los riñones, el hígado, el corazón y daños permanentes en el cerebro y el sistema nervioso. **PRIMEROS AUXILIOS:**

PIEL: Lávese meticulosamente. **OJOS:** Enjuague con abundante cantidad de agua. **INHALACIÓN:** Trasládese al aire libre. **INGESTIÓN:** NO INDUZCA EL VÓMITO. Obtenga atención médica de inmediato si surgen complicaciones debido a la exposición. **En caso de emergencia,** llame a un centro de control de envenenamiento al 1-800-222-1222. Para más información, consulte la Hoja de datos de seguridad (SDS). Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. NO INTRODUZCA EN EL CUERPO.**

ADVERTENCIA Cáncer y daños al sistema reproductor – www.P65warnings.ca.gov

QUESTIONS/¿PREGUNTAS?

Call/Llame al 1-888-DAP-TIPS or visit/
o visite dap.com & click on/ y pulse en
"Ask the Expert."

Para obtener las
instrucciones y
garantía en español,
llame al
1-888-327-8477
o visite dap.com.

DAP Products Inc.
Baltimore, MD 21224
Made in the USA for
DAP Products Inc.
with U.S. and globally
sourced materials.
dap.com