SB\_SS\_FIPAdd-A-Tee\_05\_2020\_V01 · Date issued 5/6/20

Product Submittal		
Name		
Date		
Architect/Owner		
Contractor		
Tag		
Notes		



# **FIP Add-A-Tee** Specification Sheet

## Description

1/2" FIP swivel inlet x compression outlet tee adapter allows for an additional outlet on any supply stop valve. The swivel nut threads onto the supply stop valve, then the supply lines are threaded onto the male compression outlets.

# **Specification Data**

Materials		
Body	Lead-free brass	

#### **Temperature Performance**

- Minimum working temperature 33°F
- Maximum working temperature 160°F
- Maximum working pressure 125 psi

#### **Flow Rate**

- 1/4" Compression 2.2 GPM at 20 psi
- 3/8" Compression 4.0 GPM at 20 psi
- 1/2" MIP 5.5 GPM at 20 psi

## **Part Listing**

FIPT121238Z 1/2 in. FIP Swivel x 1/2 in. MIP x 3/8 in. OD Compression Add-A-Tee

FIPT121214Z 1/2 in. FIP Swivel x 1/2 in. MIP x 1/4 in. OD Compression Add-A-Tee

#### Dimensions

Part Number	DIM A (IN)	DIM B (IN)
FIPT121238Z	0.78	1.81
FIPT121214Z	0.74	1.81

#### **Codes and Listing**

cUPC NSF/ANSI/CAN 61 NSF/ANSI 372







