





## 28055 / CH28059 / CH28051 Series


Wiring supplies as required by electrical code

TOOLS AND MATERIALS REQUIRED:










## SAFETY PRECAUTIONS:

- 1.Turn off power at main electrical service box before starting installation.
- 2.Electrical connections must comply with local code ordinances or national electrical codes. INSTALLATION:

racións prèces peuvent différer de prèces reelles Refer to the mounting bracket style that matches the bracket provided with your fixture





Step 1: Assembly. Loosen top loop and nut on center tube of fixture. Slide top loop nut and flying disc up the wire to allow room for the center tube to clear the threaded pipe. Slide center tube up until clear of threaded pipe. Ensure the ground wire (bare wire) is placed in the groove in the center of the fixture wire (insulated) and carefully slide the threaded tube down the wire until you contact the coupling. Twist threaded pipe into coupling and secure in place with nut provided. Slide center tube, flying disc and loop over threaded pipe and secure using the nut provided. Save to the control of the

Step 2: Attach chain to loop on top of fixture and to upper loop on canopy. Thread all wires through chain and feed through upper loop in canopy.

Step 3: Check electrical box to ensure it is securely attached to ceiling. If you are unsure contact a qualified electrician. Attach mounting bracket to box using screws provided or screws in the box.

Step 4: Connect ground wire to electrical box. Connect white wire from ceiling to the identified conductor (has ribs or writing on it) from the chandelier. Connect black wire from ceiling to the non identified conductor from chandelier.

Step 5: Ensure all wires are tucked inside electrical box and slide canopy carefully over mounting screws. Secure canopy in place using cap nuts provided with your fixture. (Fig 1)

Step 6: Using the rings and bars provided install the glass onto the fixture. Secure the Figure 2 CH28051 glass in place using the glass mounting rings. (Fig 2), adut at reflected rung simuot serred as

Step 7: Install proper type and wattage of bulb as per label on socket or socket ring.

Your installation is now complete, restore power and enjoy your new fixture.

Care and Cleaning

Always turn off power at the source(main electrical panel) before any type of cleaning or maintenance.

The glass can be cleaned using a soft cloth and mild dish soap. Never use abrasive pads or strong cleaning agents as this may damage the finish of the glass. Allow to dry completly before re-installing on the fixture. The fixture can be cleaned using a soft dry cloth. Never use abrasive pads or water to clean electrical fixtures.

Electrical box Ground Black Mounting Screws bracket Cap nut

(14 nu) est placé dans la rainure Figure 2 CH28055 / CH28059

