

in sink erator

Dimensions

11<sup>1</sup>/<sub>2</sub>"



in sink

Dishwasher Drain

Connection

-5'

← 6⁵/₁₀"→

\* Distance from bottom of sink to center line of disposer

outlet. Add 1/2" when stainless steel sinks are used.

to end of tailpipe. NOTE: Plumb waste line to prevent

\*\* Length of tailpipe from center line of disposer outlet

standing water in disposer motor housing.

Job Specifications

6"

## BADGER<sup>®</sup> SERIES

# Badger<sup>®</sup> 5XL

### Submittal Sheet

This model offers the following features and benefits:

- 1/2 HP heavy duty Dura-Drive<sup>®</sup> induction motor
- 1-Stage grind for a dependable grind for most food scraps
- Lift & Latch<sup>®</sup> Technology simplifies installation so the disposal can be attached with two hands
- Galvanized steel grind components and stainless steel lugs
- **3D Grind Zone** is a specially engineered grind chamber that keeps food in the grind zone and directs water to rinse chamber walls

#### Sample Specification

Food Waste Disposer(s) shall be InSinkErator Badger<sup>®</sup> 5XL, continuous feed, with 1/2 HP motor, stainless steel grinding elements with two stainless steel 360° swivel lugs. Self-service wrench.

#### Warranty

5-Year *We Come to You®* In-Home Limited Warranty<sup>1</sup>

<sup>1</sup> Visit www.insinkerator.com for warranty details.





#### 1-800-558-5700 www.insinkerator.com

### **Specifications**

Type of Feed	Continuous
On/Off Control	Wall Switch
Motor	Single Phase
HP	1/2
Volts	120
HZ	60
Amp. (Avg. Load)	6.3
Time Rating	Intermittent
Lubrication	Permanently Lubricated Upper & Lower Bearings
Shipping Weight (Approx.)	13 lbs. 10 oz. (without cord) 13 lbs. 14 oz. (with cord)
Overall Height	11-1/2"
Grind Chamber Capacity	26 oz.
Motor Protection	Manual Reset Overload
Drain Connection	1-1/2" Cushioned Slip Joint
Dishwasher Drain Connection	Yes



