

TREVINA

Ceiling mounted • Dry location listed



Description:

54" Trevina II features three blades available in Brushed Nickel finish. Coolly modern, the Trevina II ceiling fan offers both form and function with an energy efficient 17W LED source with a 3000K-color temperature. Includes a wall control switch.

Specifications:

- Brushed Nickel (-09) (plated)
- Steel construction
- Etched Opal bowl
- 52" 3 Blade Fan with LED light
- Oversized, textured die cast hanger ball reduces noise and wobble vibrations
- Mounting hardware is included
- Includes a wall control switch.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- 54 in of wire supplied
- Silver blades, plywood construction
- 12 degree blade pitch
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately. Triple capacitor speed control, manual reverse control
- Meets California Title 24 JA8-2016 Airflow: 4742 CFM*
- Energy consumption: 64 watts (excluding lights)*
- Airflow efficiency: 79 cfm/watt*
- * Fan on a downrod

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1500/88.2 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	Limited Lifetime warranty
Labels	UL Dry location listed
	Meets California Title 24 JA8-2016

P2556-0930K

Images:



Dimensions:

Diameter: 52"
Height: 15-3/4"

