

## Features

- One-piece, self-contained ceramic disc valve allows both volume and temperature control.
- Temperature memory allows faucet to be turned on and off at any temperature setting.
- Integral pull-out sprayhead with retractable hose.
- Compact three-function sprayhead with spray, aerated flow, and pause functions.
- Contemporary styling.
- 9" (229 mm) spout reach.
- 1.8 gal/min (6.8 l/min) maximum flow rate at 60 psi (4.1 bar).

## Material

- Metal construction.

## Installation

- 10-1/2" (267 mm) escutcheon plate for three-hole installation.
- Ground joint connections.
- Less flexible supplies.

## Water Conservation & Rebates

- Meets CalGreen requirements for kitchen faucets.

## Optional Accessories

- 1177879 1.5 GPM [5.7 l/min] Low Flow Kit
- 1177880 Check Valve - Flow Regulating Kit



## Codes/Standards



ASME A112.18.1/CSA B125.1  
NSF/ANSI 61  
NSF/ANSI 372  
All applicable US Federal and State material regulations  
DOE - Energy Policy Act 1992  
California Energy Commission (CEC)

## KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

## Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	CP	Polished Chrome
	VS	Vibrant® Stainless

