

ASSEMBLY INSTRUCTIONS



CAUTION

◆ Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.

◆ Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape




Phillips screwdriver



Flat blade screwdriver



Pliers



Wire strippers


HARDWARE INCLUDED




Fixture




Glass Shade



Stems



Canopy



Mounting Unit



Ball Nuts




Mounting Screws



Wire Nuts

*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE


EXPLODED PARTS



INSTALLATION


STEP 1

Unscrew the **ball nuts** from the **mounting unit**. Use the **mounting screws** to attach the **mounting unit** to the junction box.



STEP 2


Weave the fixture wire and fixture ground wire through the **stems** and **canopy**. Install **stems** based on the desired length of the item, adding **canopy** once finished.



ASSEMBLY INSTRUCTIONS (INSTALLATION)


STEP 3

Make the electrical connection from the junction box to the **fixture**. Connect the ground wire to the **mounting unit** using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied **wire nuts**. Secure with electrical tape.




STEP 4

Secure the **canopy** to the **mounting unit** with the **ball nuts**.



STEP 5

Remove the **socket ring** from the socket. Use the **socket ring** to attach the **glass shade** to the **fixture**.



STEP 6

Install bulb (not included)

