



## Interlocking 2 ft. x 2 ft. x 3/8 In. Rubber Floor Tiles 6 Pack Product Specifications

|                   |                               |
|-------------------|-------------------------------|
| Tile Size:        | 2x2 ft x 3/8 inch thick       |
| Tile Weight:      | 5.65 lb.                      |
| Material Density: | Shore A 60 +/- 5 (ASTM D2240) |
| Color:            | Black                         |
| Material:         | Recycled rubber               |
| Surfaces Install: | Flat hard surface, indoors    |
| Shipping:         | 150 per pallet                |
| Warranty:         | 5 Year limited manufacturer   |

| PRODUCT STANDARDS         |                                             |                         |
|---------------------------|---------------------------------------------|-------------------------|
| Item                      | Standard                                    | Rating                  |
| Density                   | ASTM D3676                                  | 60 pcf – 80 pcf         |
| Tear Strength             | ASTM D624                                   | 70 pli min – 80 pli min |
| Elongation                | ASTM D412                                   | >145% – 300%            |
| Tensile Strength          | ASTM D412                                   | 200 PSI – >220 PSI      |
| Flexibility               | ASTM F137 1/4" Mandrel                      | Pass                    |
| Resistance to Chemicals   | ASTM F925                                   | No change               |
| Force Reduction           | ASTM F2772                                  | 12.9% – 13.7%           |
| Energy Restitution        | ASTM F2772                                  | 85% – 86%               |
| Abrasion Resistance       | ASTM D3389                                  | <1.7g, 1000 cycles      |
| Static Load Limit         | ASTM F970                                   | 0.001" @ 250 PSI        |
| Coefficient of Friction   | ASTM D2047                                  | >0.95                   |
| Slip Resistance           | ASTM F2772                                  | Pass                    |
| Pill Test                 | ASTM D2859                                  | Pass                    |
| VOC Compliant             | ASTM D5116 / CA 1350                        | Yes                     |
| LEED Qualification        | Qualifies for Material and Resources Credit |                         |
| Rolling Load              | EN1569                                      | Pass                    |
| Resistance to Impact      | EN1517                                      | 14 N/m                  |
| Resistance to Indentation | EN1516                                      | 0.1mm                   |
| Vertical Deformation      | ASTM F2772                                  | 1.4mm                   |
| Environmental Product     | ISO14025 / UL Environmental                 | Doc. #: -101047-4150    |

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
Toll free: 877-822-6622  
Fax: 715-825-4928  
info@greatmats.com