

**Model WT2 UL Listed Wire Combinations Strip Wires 3/8 in., #16 and smaller  
UL File Number E5238**

**Copper to Copper wire only (do not use on aluminum)**



**300 Volt Maximum - For use with solid or stranded combinations**

|                            |                                     |  |  |
|----------------------------|-------------------------------------|--|--|
| <b>1 #14 Stranded only</b> | <b>1 #16 w/1 to 3 #18</b>           |  |  |
| <b>1 #16 Stranded only</b> | <b>1 #16 w/1 #18 w/1 #20</b>        |  |  |
| <b>2 or 3 #16</b>          | <b>1 #16 w/1 to 4 #20 or #22</b>    |  |  |
| <b>1 #18 Stranded only</b> | <b>4 #18 w/1 #20 or #22</b>         |  |  |
| <b>2 to 4 #18</b>          | <b>3 #18 w/1 or 2 #20 or #22</b>    |  |  |
| <b>3 to 5 #20</b>          | <b>2 #18 w/1 to 3 #20 or #22</b>    |  |  |
| <b>1 #14 w/1 #16</b>       | <b>1 #18 w/2 to 4 #20</b>           |  |  |
| <b>1 #14 w/1 or 2 #18</b>  | <b>1 #18 w/3 or 4 #22</b>           |  |  |
| <b>1 #14 w/1 to 3 #20</b>  | <b>4 #20 w/1 #22</b>                |  |  |
| <b>1 #14 w/1 to 4 #22</b>  | <b>3 #20 w/1 or 2 #22</b>           |  |  |
| <b>2 # 16 w/1 #18</b>      | <b>2 #16 w/1 #20 w/1 #22</b>        |  |  |
| <b>2 #16 w/1 or 2 #20</b>  | <b>1 #16 w/1 #22 w/1 #18 or #20</b> |  |  |
| <b>2 #16 w/1 to 3 #22</b>  | <b>1 or 2 #18 w/1 #20 w/1#22</b>    |  |  |
|                            |                                     |  |  |