


How-To Build a Planter/Mailbox

Featuring Quarry Wall

Building your perfect outdoors isn't always about constructing luxuries, sometimes its about building something that's as stunning as it is practical. All it takes is a few easy steps to make this awesome accent piece the hallmark of your front yard, with no stone cutting required.



- Make sure your chosen site is clear of underground utilities and that you understand all local rules and ordinances.
- Excavate a hole that is 1ft across and 2ft deep.
- Fill the first 8 inches of hole with Fast-Setting Concrete.
- Place your pole in the concrete and make sure it's level. Once adjusted, pour the remaining concrete to fill the hole.



- Start laying your blocks, with each block touching end to end. Form your entire square then use the last three blocks to enclose the mailbox post.
- Use a Rubber Mallet and Level to align blocks and make any necessary adjustments.



TIP: Make sure to lay the blocks with the finished side facing outward and don't repeat blocks with similar looks.



 Apply Construction Adhesive before laying next row, and add blocks to create a second layer.



TIP: Keep the joints offset and the face pattern random.



 Apply adhesive to blocks and lay a third layer, with the same face style pattern as the first layer.



 Keep laying blocks with adhesive to form an additional 3 layers around mailbox post only, while alternating face styles.



Using your **Rubber Mallet**, check again that the back unfinished sides of blocks on the inside of planter line up vertically.



Set and glue **Caps** to the tops of the wall blocks.



SUPPLIES LIST:

- o 48 Quarry Wall Blocks
- o 13 Caps 12" x 18"
- o Tape Measure
- o Shovel
- o Fast-Setting Concrete Mix
- o Rubber Mallet
- o Level
- O Construction Adhesive

STYLE TIP: Add finishing touches, like affixing the mailbox to post and fill planter with soil and seasonal plants. You can even attach your home address number to accentuate your personal taste.





