



Finesse™ Peak®

Frameless sliding shower door

547808-48

Features

- Frameless
- 5/16" (8 mm) thick tempered glass
- CleanCoat®+ glass coating creates a hydrophobic barrier that repels water, soap scum, and residue, saving time and protecting shower doors 10 times longer than original CleanCoat. (Based on 2021 internal wear/abrasion testing using a microfiber cloth.)
- Vertical blade handles complete the look of this door
- Tempered glass ensures enhanced safety and durability

Material

- Stainless steel hardware prevents rust and corrosion

Installation

- Out-of-plumb adjustability simplifies installation
- Not for use in hospitality
- For residential use only



Codes/Standards









ANSI Z97.1
CAN/CGSB-12.1
CPSC 16CFR 1201

STERLING® Bath and Shower Doors Five-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	DR	Deep Bronze
	DR	Deep Bronze
	N	Nickel
	N	Nickel
	PBL	Matte Black
	PBL	Matte Black
	S	Silver
	S	Silver

Available Glass Options


Code	Description
G05	Clear
G03	Frosted

1-800-STERLING (1-800-783-7546)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.sterlingplumbing.com.

7-31-2024 21:14 - US/CA



Technical Information

All product dimensions are nominal.

Base-To-Wall	$\frac{1}{2}"$ (13 mm)
Radius – Max:	
Shower Ledge Min	$2\frac{1}{8}"$ (54 mm)
Flat:	
Shower Wall Min	$2\frac{3}{8}"$ (60 mm)
Flat:	

Notes

Install this product according to the installation guide.

NOTICE: The vertical opening should be a minimum of 72" (1829 mm) to allow clearance for installation.