



**WHITE  
(TINTABLE)**

# DRYLOK®

## ORIGINAL

**CONCRETE & MASONRY  
WATERPROOFER**

**GUARANTEED TO PROTECT** ▶ **Against water seepage,  
leaks, and dampness**

Sandy texture, tintable	Interior/exterior latex
Apply by  	Proven protection for basement walls and building exteriors

**10 YEAR WARRANTY**

### INTERIOR PROTECTION



**10 PSI** RESISTS HYDROSTATIC PRESSURE

### EXTERIOR PROTECTION



**RESISTS 98 MPH WIND-DRIVEN RAIN**

DOES NOT EXCEED  
MAXIMUM VOC 100 g/L



### DRYLOK® ORIGINAL CONCRETE & MASONRY WATERPROOFER

DRYLOK® is an easy way to deal with water seepage problems. Formulated for waterproofing all interior/exterior, above/below grade masonry including cinder and concrete block, stucco, and brick. Tested to ASTM D-7088 Resistance to Hydrostatic Pressure and ASTM D-6904 Resistance to Wind-Driven Rain. Resists 10 PSI, greater than a wall of water 22 feet high! Fully transferable 10 year warranty\*.



**PATCH:**  
Holes and cracks



**DRYING TIME  
AND RECOAT:**  
2-3 hours



**COVERAGE:**  
1<sup>st</sup> coat: 75 sq. ft.  
per gal., 2<sup>nd</sup> coat:  
75-100 sq. ft.  
per gal.



**CLEAN-UP:**  
Use warm,  
soapy water

**SURFACE PREPARATION:** Surface must be clean and free from dirt, dust, grease, oil, form release compound, or paint. Old paint in poor condition must be removed by using suitable means. Not recommended for use on horizontal surfaces subject to foot traffic (use DRYLOK® Floor & Wall Masonry Waterproofer). Patch all holes or cracks and the floor/wall joint with DRYLOK® FAST PLUG®, a fast-setting hydraulic cement, and smooth the patch evenly with the surface. EFFLORESCENCE, a white, powdery, crystal-like deposit visible on the masonry surface, must be removed. DRYLOK® ETCH, used according to manufacturer's directions, is an effective efflorescence removal agent. If the surface is slightly damp, wet, or efflorescence troubled, apply DRYLOK® WET WALL BONDING PRIMER to troubled areas according to the label instructions. If applied to a bare masonry surface, this will not void the warranty.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION:** STIR THOROUGHLY BEFORE AND DURING APPLICATION. DO NOT THIN. Air and surface temperatures must be 50°F (10°C) or higher. Best results are obtained when applied over dry surfaces. Wait for a dry (rain-free) period to apply. It is recommended to test the product in a small area prior to full application to ensure the desired effect is achieved. Apply with a roller [3/4" (19mm) nap] or DRYLOK® BRUSH. If rolled, back brush the first coat to fill pinholes. If brushed, work the DRYLOK® into the pores of the masonry, making sure to fill all pores and pinholes (see COVERAGE). APPLY TWO COATS. Allow to dry 2-3 hours between coats. DRYLOK® is an ideal finish coat. However, for decorative purposes, you can apply a good quality latex paint. Wait 24 hours before applying any decorative top coat.

**IMPORTANT:** If leaking is still present after two coats, it indicates that pores or pinholes are still open. These areas should be painted again. When painting the inside of concrete fish ponds and non-potable water tanks, allow DRYLOK® ORIGINAL CONCRETE & MASONRY WATERPROOFER to dry at least one week before putting into service.

UNITED GILSONITE LABORATORIES, 1396 Jefferson Ave., Dunmore, PA 18509  
Order No. 27513 UFI: QCQS-3WW9-170W-R81C LR523 [www.DRYLOK.com](http://www.DRYLOK.com)

**TINTING:** DRYLOK® can be tinted to light shades with universal tinting colorants. Use only 25% of color normally recommended. Do not use more than 2 fl. oz. (59mL) per gallon.

**WARNING!** Vapor harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Overexposure may cause lung and kidney damage.

**Cancer hazard: Contains Crystalline Silica**, which can cause cancer. (Risk of cancer depends on duration and level of exposure.) Close container after each use. Causes eye, nose, and throat irritation. May be harmful if absorbed through skin. Harmful if swallowed. Do not take internally.

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **Use only with adequate ventilation.** Do not breathe vapors. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates vapor levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not get in eyes, on skin, or clothing. Wash thoroughly after handling.

**First Aid:** In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes, call poison control center, hospital emergency room, or physician immediately; for skin, wash thoroughly with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, call poison control center, hospital emergency room, or physician immediately. If swallowed, do not induce vomiting. Call poison control center, hospital emergency room, or physician immediately.

**KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING.**

If spilled, contain spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**\*WARRANTY:** DRYLOK® ORIGINAL CONCRETE & MASONRY WATERPROOFER, when applied according to directions on a properly prepared bare masonry surface, is warranted to provide a waterproof coating for ten (10) years from date of sale, warranty includes subsequent owners, or we will refund the cost of the DRYLOK®. This is the exclusive remedy. Excludes leaks due to cracking of the surface, recurring efflorescence, and application over surfaces previously coated with a paint other than DRYLOK® Masonry Waterproofer. **ANYONE HANDLING THIS PRODUCT CAN VISIT OUR WEBSITE AT [www.UGL.com/warranties](http://www.UGL.com/warranties) TO REVIEW AND DOWNLOAD COMPLETE DETAILS OF THE WARRANTY'S TERMS AND CONDITIONS.**

