

## QC ES-7000 Specifications

Air Flow	Hi: 6,878 CFM / Low: 4,304 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 5,170 CFM / Low: 3,150 CFM	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 2,293 SQFT to 3,439 SQFT	
Energy Use	Hi: 727 Watts / Low: 164 Watts	
Amps	Hi: 8.96 / Low: 2.32	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	2	
dBA	Hi: 51.7 / Low: 41.4	
Minimum Attic Clearance	44"	
Duct Diameter	24"	
Duct Length	9 feet	
Motor Head Diameter	24 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Recommended: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	9.18 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	95 lbs.	
Box Dimensions	41" x 28" x 39"	
In The Box	<div> <div>-QC ES-7000 Motorhead</div> <div>-Ceiling Grille</div> <div>-Cut-out Template</div> <div>-Window Locks</div> </div> <div> <div>-Damper Box</div> <div>-9 Foot Duct</div> <div>-Accessory Bag</div> </div>	



For more information, visit our website at:  
**QUIETCOOLSYSTEMS.COM**

**QC ES-7000**  
**QuietCool Energy Saver Line**