

Slip Doctors®

LEADERS IN FLOOR SAFETY

POLISH GRIP

ANTI-SLIP PENETRATING SEALER

FOR USE ON:


Marble - Granite

Highly Polished Tiles

Coverage up to 2,400 SQ FT

ONE GALLON / 3.78 LITER

DANGER! - Toxic if inhaled. May be fatal if swallowed and enters airways. Flammable liquid and vapor.



SlipDoctors® Polish Grip is a professional-grade penetrating sealer designed to provide anti-slip protection on unsealed natural stone, polished porcelain tile, marble, granite, concrete and other acid-sensitive surfaces. This easy-to-apply treatment forms an invisible barrier that increases traction and improves resistance to spills and stains. Once applied, the lustrous natural shine remains unchanged. For use on interior and exterior surfaces.

SURFACE PREPARATION

- Clean surface thoroughly with pH-neutral cleaner.
- Surface must be clean and completely dry before application. For optimal results, apply when surface is dry and free from moisture from rain, humidity and other conditions.
- Protect exposed surfaces including wood, carpet, metal and landscaping.



APPLICATION INSTRUCTIONS

1. Read label thoroughly before application.
2. Sample testing is recommended to assure maximum performance and suitability for the intended use. Test product in an inconspicuous area and allow to fully cure to test results.
3. Do not thin or dilute. Pour Polish Grip into a separate container. Apply Polish Grip evenly to surface in a thin layer using a clean white towel, microfiber towel or Polish Grip Applicator. Leave on surface for 3 – 5 minutes for maximum penetration.
4. Using light strokes, gently remove any excess product with a clean white towel, microfiber towel or carpet bonnet before product dries. Any excess residue that dries on the surface can be removed by re-applying a small amount of Polish Grip and immediately wiping off excess while wet.
5. If a second application is desired, allow 2 – 4 hours before re-applying.
6. Polish Grip will dry to the touch in 4 – 6 hours. Do not walk or touch surface until dry to the touch. Allow 24 – 72 hours to fully cure.
7. Re-application may be necessary every 6 – 12 months depending on conditions, traffic levels and flooring surface.



Scan for
instructions



MADE IN USA

MAINTENANCE: Clean regularly using a pH-neutral cleaner. Using heavy industrial cleaning methods or equipment may decrease product performance.

PRECAUTIONS: Wear protective gloves, protective clothing, eye protection and face protection. Avoid breathing dust, fumes, gas, mist, vapors or spray. Use in a well-ventilated area. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground or bond container and receiving equipment. Use only explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Store in upright position and protect from freezing. **KEEP OUT OF REACH OF CHILDREN AND PETS.**

FIRST AID: In all cases of doubt, seek medical attention.

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. **SKIN:** Remove contaminated clothing and launder before reuse. Wash with soap and water. Seek medical attention if symptoms persist. **INHALATION:** Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Seek medical attention. **INGESTION:** Do not induce vomiting. Seek medical attention. Never give anything by mouth to an unconscious person.

DISPOSAL: Dispose of container and unused contents in accordance with regional, national and local laws and regulations.

Find more anti-slip products at www.SlipDoctors.com. Need technical assistance? Call 888-436-5404 or email us at support@slipdoctors.com.

UN1268
PETROLEUM
DISTILLATES,
n.o.s, CL 3, PG III



DANGER

