



# CAPITOL®

## 1/4" CORK UNDERLAYMENT SHEETS

### 110622

#### SOUND ABSORBING

Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below

#### CRACK SUPPRESSION

Acts as a crack isolation membrane that resists transfer of stress cracks from suboor through to flooring surfaces

#### INSULATING

Reduces thermal transmission, increasing effectiveness of floor heating systems

**R-Value**  
0.74

1/4"  
(6 MM)

#### EASY TO INSTALL

In both glue-down and loose lay configurations\*\*

**IIC STC Δ**  
74\* | 70\* | 22

\*Ceramic tile on a 6" concrete slab with a suspended ceiling

#### VERSATILE

For use under ceramic tile, stone, engineered hardwood and laminate floors



CERTIFIED BY  
SCS Global Services

\*\*For a list of recommended adhesives to use for glue-down installations, please go to [capitolflooringproducts.com](http://capitolflooringproducts.com) or call 866-435-8665.

ITEM #	DESCRIPTION	QTY	SIZE	COVERAGE
110622	1/4" (6 mm) Sheets	25 sheets	2' x 3'	150 sq. ft./case

Our Natural Cork products may contribute towards satisfying credits under the LEED® Green Building Program in the following areas:

MR 4.1 - 5% Recycled Content of total building materials (post consumer + 1/2 of post industrial)

MR 4.2 - 10% Recycled Content of total building materials (post consumer + 1/2 of post industrial)

MR 6 - Specifying rapidly renewable building materials for 5% of total building materials.

EQ 4.1 - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)