

Pivot LED

Wall or Ceiling Mounted • Damp Location Listed **PROGRESS LED**

Description:

Pivot LED Four-Light Matte Black Modern Semi-Flush or Wall Mount Fixture

Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.125 in W., 1.25 in ht., 5.125 in depth
- Mounting backplate for outlet box included
- 6 in of wire supplied

Performance:

Number of Modules	4
Input Power	17.5 W
Input Voltage	120 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	930/53 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed
	Meets California Title 24 JA8-2016

P350230-31M-30



Dimensions:

Diameter: 25 in
Height: 4-3/8 in

Photometrics:

ELECTRICAL DATA		P350230-31M-30
Input Voltage		120 VAC
Input Frequency		60 Hz
THD		<20%
EMI/RFI		FCC Title 47, Part 15, Class B
Operating Temperature		-30 °C to 30 °C
Dimming		Yes*
Over-voltage, over-current, short-circuit protected		
*See Dimming Notes for more information		

P350230-31M-30

P350230-31M-30

Dimming Notes:

P350230-31M-30 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron NTEVL-300

Lutron DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.