

The image contains three technical drawings of a window unit:

- Top View (Front Elevation):** Shows a rectangular window unit with overall dimensions of 44.00 (height) by 48.00 (width). The unit is surrounded by a dashed-line framing. Key dimensions include:
 - Top framing: 22.00 (from top edge to top of unit) and 48.00 (from top edge to bottom of unit).
 - Right framing: 40.13 (from right edge to right of unit) and 48.00 (from right edge to left of unit).
 - Bottom framing: 3.00 (from bottom edge to bottom of unit).
 - Section lines A-A and B-B are indicated.
- Right Side View (Section B-B):** Shows the side profile of the window unit with a height of 43.00. The top and bottom framing are 0.50 thick. The total width of the unit and its immediate framing is 5.75.
- Bottom View (Detail Section):** Shows a cross-section of the window unit's base. Key dimensions include:
 - Overall height: 17.00.
 - Top framing: 0.50 thick.
 - Base framing: 12.00 wide.
 - Redi Flash®: A flashing material installed over the base splash wall.
 - Unit width: 47.00.
 - Bottom framing: 0.50 thick.
 - Bottom framing: 0.38 wide.
 - Bottom framing: 5.50 wide.
 - Bottom framing: 2.1 high.
 - Bottom framing: 0.50 thick.