

### Features

- Metal construction.
- Cross handles.
- NEW Quick-Connect hose connections make widespread faucet installation a snap.
- Handles pre-assembled on valves simplify installation.
- Leak-free ceramic disc valves exceed industry standards by two times for a lifetime of use.
- Stationary spout.
- For 8" (203 mm) or 16" (406 mm) centers.
- Durable KOHLER finishes resist corrosion and tarnishing.
- Complete range of faucets, accessories and showering components to coordinate a full bathroom.
- 1.2 gal/min (4.5 l/min) maximum flow rate [max at 60 psi (4.1 bar)]



ADA

### Codes/Standards



ASME A112.18.1/CSA B125.1  
All applicable US Federal and State material regulations  
DOE - Energy Policy Act 1992  
EPA WaterSense®  
California Energy Commission (CEC)  
ADA  
ICC/ANSI A117.1


### KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

### Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	CP	Polished Chrome
	TT	Vibrant Titanium



### Technical Information

All product dimensions are nominal.

Valve body: Machined Brass

Drain with overflow: YES

Drain tailpiece: YES

included:

### Spout:

Spout reach: 5-15/16" (151 mm)

Handle clearance: 1-1/2" (38 mm)

### Faucet:

Flow rate: 1.2 gal/min (4.5 l/min)

Pressure: 60 psi (4.1 bar)

### Notes

Install this product according to the installation guide.

ADA compliant when installed to the specific requirements of these regulations.