



1128QC: 6" New Construction IC Recessed Housing with "Quick Connects"



Dimensions:

Diameter:	6 3/8"
Length:	13 1/2"
Width:	10 3/4"
Height:	7 7/8"

Features:

- Easily converts to LED with optional replacement lamps
- Meets Title 24 energy efficiency standards

Material List:

1 Housing - Aluminum -

Safety Listing:

Safety Listed for Damp Locations
Safety Listed for Damp Locations

Instruction Sheets:

Bilingual (English - French) (HC-438FB)

Collection: Recessed Lighting

This IC recessed light housing features an air-tight application providing quality illumination while offering energy efficiency and lower operating costs. Also features "Quick Connect" wiring for ease of installation.

This IC recessed light housing features an air-tight application providing quality illumination while offering energy efficiency and lower operating costs.

QC - includes Quick Connect wire connectors for easy installation

Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Joist Tab: Tab to locate on bottom of joist.

Notch for T-Bar Ceilings: No clips required. Secure bar hanger to T-Bars with wires or screws.

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Quick Hit: Integral captive nails included and positioned for fast, easy installation.

Hinged Door: The hinged junction box door allows full access for wiring while remaining attached to the recess housing.

Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.

Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in. 4 out #12 wire, saves installation time.

Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

UPC #:785652011283

Finish: Not Applicable ()

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual	1128QC	1	785652011283	14.75	10.75	8	0.734	2.55	100	Yes
Master Pack		6	10785652011280	22.25	20	8.75	2.253	18.15	100	Yes
NJ Pallet		192		48	40	75	83.333	580.8		No
NV Pallet		192		48	40	75	83.333	580.8		No

Trim



1120-15
6" Open Trim

White Steel Trim
Maximum Wattage:
75w PAR30L
65w BR30
13.5w A19
15w PAR30L
15w BR30



1125-14
6" Aluminum Baffle Trim

White Trim / Baffle Aluminum Baffle
White Trim / Baffle Aluminum Trim
Maximum Wattage:
50w PAR30S
75w PAR30L
65w BR30
13.5w A19
15w PAR30L
15w BR30



1126-14
6" Steel Baffle Trim

White Trim / Baffle Steel Baffle
Maximum Wattage:
50w PAR30S
75w PAR30L
65w BR30
13.5w A19
15w PAR30L
15w BR30



1126-15
RECESSED TRIM

Black Steel Baffle
White Steel Trim
Maximum Wattage:
50w PAR30S
75w PAR30L
65w BR30
13.5w A19
15w PAR30L
15w BR30



1133AT-15
6" Flat Glass Shower Trim

White Glass Diffuser
White Plastic Trim
Maximum Wattage:
40w A19
8w A19
Suitable For Shower Light



1134-68
6" Drop Acrylic Shower Tr

White Plastic Plastic Diffuser
White Plastic Trim
Maximum Wattage:
40w A19
8w A19
Suitable For Shower Light



1135AT-15
RECESSED TRIM

Smooth White Glass Diffuser
White Steel Trim
Maximum Wattage:
40w A19
8w A19



1136-15
6" Eyeball Trim

White
White Steel Trim
Maximum Wattage:
75w PAR30L
65w BR30
15w PAR30L
15w BR30



1136AT-15
6" Eyeball Trim

White
White Steel Trim
Maximum Wattage:
75w PAR30L
65w BR30
15w PAR30L
15w BR30



1151AT-14
6" Baffle Trim

White Trim / Baffle Aluminum Trim
Maximum Wattage:
50w PAR30S
75w PAR30L
90w PAR38
65w BR30



1151AT-15
RECESSED TRIM

Black Aluminum Baffle
White Aluminum Trim
Maximum Wattage:
50w PAR30S
75w PAR30L
90w PAR38
65w BR30



1154AT-14
6" Open Cone Shower Trim

White Trim / Baffle Aluminum Baffle
White Trim / Baffle Aluminum Trim
Maximum Wattage:
50w PAR30S
75w PAR30L
90w PAR38
Suitable For Shower Light



1155AT-15

6" Fresnal Glass Shower T

Clear Glass Lens

White Aluminum Trim

Maximum Wattage:

40w A19

8w A19

Suitable For Shower Light