

Professional Products, Professional Results

١

## THE SMARTEST SOLUTION IN MOLD RESISTANT COATINGS.

The best just got better. New and improved IAQ 6000 is a white/tintable mold resistant coating containing a sustainable fungistatic agent to resist mold growth on the dry coating surface. IAQ 6000 is preferred by restoration professionals and has received the highest scores possible in both ASTM G-21 and ASTM D-3273 mold resistance testing by independent laboratories.



\* 1.7 g/L (calculated as per EPA) / 6 g/L (calculated as per SCAQMD)

## NEW 8360-5 IAQ 6000 5 GALLON

1

- Yields better results with 1 coat than competing products achieve with 2 coats
- A South Coast Air Quality Managment District (SQAQMD) Super-Compliant coating
- Use on wood, plaster, wallboard, sheetrock, concrete, masonry, and primed meta

- Ideal for AIA/CSI 02 87 13 or 02 85 00 Mold Remediation
- Proprietary and sustainable new zinc complex active ingredient
- Exceeds requirements of IICRC S520 for fire testing, permeability, VOCs, and resistance against mold regrowth



FBC<sup>™</sup> System Compatible indicates that this product

has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology." "FBC™, Flow-Guard Gold®, BlazeMaster® Corzan®, and TempRite® are trademarks of The Lubrizol Corporation or its affiliates.

## **SAVE MONEY!** Twice The Coverage = Half the Labor.

IAQ 6000 contains a more effective mold resisting active ingredient and more solids per volume than competing products. One coat of IAQ 6000 hides much better and is more effective against mold than two coats of competing products.

|                           | FIBERLOCK<br>IAQ 6000       | COMPETITOR   |
|---------------------------|-----------------------------|--|
| 1st<br>Coat               | \$0.50 / Sq.ft.             | \$0.50 / Sq.ft.  |
|                           | \$0.26 / Sq.ft.             | \$0.17 / Sq.ft.  |
|                           | \$0.76 / Sq.ft.             | \$0.67 / Sq.ft.  |
| LABOR                     | 104                         | \$0.50 / Sq.ft.  |
| 2nd LABOR<br>Coat COATING |                             | \$0.17 / Sq.ft.  |
|                           |                             | \$0.67 / Sq.ft.  |
| TOTAL                     | \$0.76 / Sq.ft.             | \$1.34 / Sq.ft.  |
|                           | COATING<br>LABOR<br>COATING | ISON IAQ 6000<br>LABOR \$0.50 / Sq.ft.<br>COATING \$0.26 / Sq.ft.<br>\$0.76 / Sq.ft.<br>LABOR<br>COATING |

IAQ SAVINGS: 43% / Sq.ft.

Labor is the most expensive part of restoration projects. IAQ 6000 acheives superior performance in a single coat saving in excess of 23% in material cost per square foot, with a 50% reduction in labor.



IAQ 6000 may cost more up front, but it can help avoid costly call backs. The use of lower quality coatings that fail to prevent bacterial re-growth can lead to a complete tear out/reconstruction incurring massive labor and material expenses.

For additional information and for technical and safety data sheets, please visit www.Fiberlock.com





ASTM D3273 ANTI-MICROBIAL TEST RESULTS (4 WEEKS)



ASTM D3273 ANTI-MICROBIAL TEST RESULTS (4 WEEKS)



## WWW.ICPGROUP.COM | WWW.FIBERLOCK.COM